

A1 heavy duty spray adhesive

The Morley Heavy Duty Spray is truly heavy duty. It is a multi-functional adhesive used for the perimeter fixing of most types of carpets, tiles, underlays & associated products. It is CFC free and has an adjustable nozzle, allowing different thickness of band to be sprayed.

USES

It is used to fix foam backed carpets, carpet tiles, carpet and foam underlays, felt textiles and fabrics.

SUBFLOORS

Suitable sub-floors include concrete, stone, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring. With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

Ensure that surfaces are clean, dry and dirt free. Shake can well before use.

APPLICATION

Spray the adhesive evenly from a distance of 10-20cms. For a strong bond, spray a number of light coats on both surfaces. For a lighter bond apply to one surface only. Allow approx. 1-5 mins for the adhesive to become tacky, then press surfaces together firmly, working outwards from the centre to adhere a good bond. Excess adhesive can be removed with white spirit.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given. Ensure area of use is well ventilated. Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves. In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help. If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.



TECHNICAL SPECIFICATION

PRODUCT CODE - A1

PRODUCT NAME - Heavy Duty Spray Adhesive

CONTAINER SIZE - 500ml aerosol can

OPEN TIME - 1-5 mins depending on temperature, humidity and sub floor porosity.

STORAGE - Store between temperatures of 5°C and 25°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

CLEANING - Overspray can be removed with a small amount of white spirit. Always test before going ahead.

Health and Safety Sheets available on request.