

Uniclass L5391:L673		EPIC E4:F73	
CI/SfB	(43)	Yt3	

August 2010 Edition No.7

morleys
limited



***Flooring
Adhesives***



Introduction

Morleys have been manufacturing flooring accessories since 1986. Over that time the product range has continued to expand and has proved to be of excellent quality and is readily available to the marketplace through a network of stocking flooring distributors throughout the country.

As a progressive British manufacturer who carries extensive back-up stocks, we pride ourselves in being able to offer a service that is second to none at prices that are more than competitive.

Continuous research and development is undertaken to establish our range of flooring adhesives. Extensive testing is carried out to provide the floorcovering installer with products that are not only user friendly but also of outstanding quality and value for money.

Should you have any queries regarding our products and services, please do not hesitate to contact us on :

Telephone : 01772 626700

Fax : 01772 627372

On Line: www.morleysltd.co.uk

E-mail: sales@morleysltd.co.uk

telephone: 01772 626700

Contents

General Information	a
Adhesive Trowels	1
JM100 Carpet Seaming Adhesive	2
JM200 Peelbond Tackifier	3
JM300 Surface Tackifier	4
JM400 Multi Purpose Adhesive	5
JM500 Acrylic Adhesive	6
JM600 Latex Adhesive	7
JM700 Premium Pressure Sensitive Adhesive	8
JM800 Spray-on Contact Adhesive	9
JM900 Entrance Matting Adhesive	10
JM1000 Universal Primer	11
A1 Heavy Duty Spray Adhesive	12
A2 Heavy Duty Gripper Adhesive	13
A3 Heavy Duty Vinyl Spray Adhesive	14
A17 Fast Setting Gripper Adhesive	15
Recommended User Guide	16



General Information



The information in this guide has been prepared to assist specifiers and installers select the most suitable adhesive for their installation. As floorcovering manufacturers, in their pursuit of improvements, introduce changes to their products and ranges, it is not possible to take account of all these changes. In any installation, site conditions can vary, and therefore the user must ensure the suitability of our products by enquiry or the carrying out of appropriate tests.

Installation Requirements

All parts of the installation should comply with the latest edition of the following:
BS 5325 The Installation of Textile Floorcoverings.
BS 8203 The Installation of Resilient Floorcoverings
BS 8102 Protection of buildings against water from the ground.

Another useful source of reference is:
The C F A Guide to Contract Flooring.

Subfloor Preparation

Subfloors must be prepared in accordance with the floorcovering manufacturer's recommendations. Direct to earth bases must incorporate an effective damp proof membrane. Underfloor heating must be switched off for 48 hours before and after the installation. Subfloors should be sound, smooth, clean, dry and free from any contamination that will affect adhesion. Relative humidity of cementitious subfloors should be 75% or less (when tested by the method described in BS 8203). Very absorbent surfaces should be primed with a suitable sealer. Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plywood, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

**There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g. moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation. Please contact office for technical information. With existing well bonded resilient flooring, care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

For best results a minimum temperature of 18°C (65°F) should be maintained for the installation.

Adhesive Selection

This guide contains adhesive recommendations for specific floorcoverings but this does not exclude floorcoverings not listed. For floorcoverings not listed we recommend the installer speak with the Technical Department at Morleys or carry out appropriate tests to prove suitability. Further guidance on the suitability of an adhesive can be found on the Adhesive Data Sheets.

For releasable bonds, it should be understood that several factors play an important part in the final bond strength including :amount of adhesive applied, porosity of both subfloor and floorcovering, and whether or not the adhesive is completely dry. Failure to take these into account can result in either a permanent bond or no bond at all.

For permanent bonds, most important considerations after selection of adhesive are the correct selection of trowel, use of appropriate open time, and application of either weighted roller or glider to the installed floorcovering. For ALL applications, read the label on the tub, read the appropriate Product Data Sheet and the Health and Safety Data Sheet.

Health and Safety

In accordance with the requirements of Section 6 of the Health and Safety at Work Act, information is provided for our customers to ensure (as far as is reasonably practicable) that they can meet their legal obligations under the Act.

Individual Health and Safety Data Sheets on all of our adhesives are available on request. Certain Health and Safety information is also provided on Product Data Sheets and on product labels.

Important Notes

LIMITED WARRANTY- made in lieu of all other warranties, expressed or implied. Morleys Adhesives are guaranteed against manufacturing defects. Any goods proven to be defective within 1 year of manufacture will be replaced or purchase price refunded. MORLEYS LTD will not be responsible for damages in excess of purchase price. User to decide suitability of product use.

If there is any doubt over any aspect of any Morley Adhesive, its use or application please contact:

MORLEYS LTD Unit 2, Higher Walton Mill,
Higher Walton, Preston PR5 4DJ



Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3

MT-16220, MT-A1, MT-A2, MT-B1, MT-B2, MT-SW1 Adhesive Trowels

MT-16220	Detachable Handle
MT-A1	Small Notched Trowel Blade
MT-A2	Medium Trowel Blade
MT-B1	Large Trowel Blade
MT-B2	Extra Large Trowel Blade
MT-SW1	Screeding Blade

MT-16220

Detachable handle can be used with any of the above blades. The main advantage of this system is the quick change handle, which can be detached in seconds by sliding the handle off the blade without the need for tools.

One handle is all the contractor requires to fit all our blades, saving the contractor time and money not having to purchase a number of trowels with traditional handles.

MT-A1

Notch size: Depth 1.00mm, width 1.50mm, tooth width 0.5mm. This is the smallest notched trowel and suitable for applying JM700 for installing decorative vinyl tiles and planks. This can be applied directly to the floor and left to dry for pressure sensitive applications, without the need to roll out the peaks with a wetted paint roller, therefore, saving the flooring contractor time.

MT-A2

Notch size: Depth 1.58mm, width 1.58mm, tooth width 1.58mm. The A2 trowel is recommended for the installation of vinyl sheet and tiles in conjunction with JM500 Acrylic Adhesive. The A2 will apply the same amount of adhesive as a 1.5mm x 5mm adhesive trowel.

MT-B1

Notch size: Depth 2.38mm, width 2.38mm, tooth width 2.38mm. The B1 trowel is used to apply JM400 Multi-Purpose Adhesive and is recommended for the installation of carpets. The B1 is equivalent to the 2mm x 6mm adhesive trowel.

MT-B2

Notch size: Depth 3.18mm, width 3.18mm, tooth width 1.58mm. MT-B2 is the largest notched trowel and is designed for the application of JM400 Multi-Purpose Adhesive. MT-B2 is designed for the application of adhesive for rough or ribbed backed carpeting; when more adhesive is required to achieve the correct amount of adhesive transfer. The MT-B2 trowel is equivalent to a 3mm x 6mm adhesive trowel.

MT-16220
Detachable
Handle



MT-A1
Blade



MT-A2
Blade



MT-B1
Blade



MT-B2
Blade



MT-SW1
Screeding
Blade



Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3



JM100

Carpet Seaming Adhesive

For seaming woven, secondary, high density rubber foam and polyurethane foam backed carpets.



USES

To be used in conjunction with JM400 multi-purpose adhesive for securing and joining the edges of carpets to prevent carpet seams opening and fraying. To be used for seaming woven, secondary, high density rubber foam and polyurethane foam backed carpets.

PREPARATION

Pour JM100 seam sealer adhesive into plastic dispenser bottle, cut the nozzle to create 2mm opening and place the cap over the nozzle to prevent the JM100 from drying out.

APPLICATION

Carpet seams must be cut dry and butted together; fold back both edges of the carpet and apply JM400. Place one side of the carpet into the JM400; remove the cap from the plastic dispenser bottle and apply a bead of JM100 along the entire seam, carefully place the neighbouring seam into the adhesive and avoid squeezing the JM100 onto the top fibres of the carpet. Replace the cap on the plastic dispenser bottle. When the installation is complete pour the JM100 back into the screw top JM100 tin, do not store JM100 in the plastic dispenser bottle.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet.
Ensure area of use is well ventilated.
Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.
In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.
If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.

TECHNICAL SPECIFICATION

PRODUCT CODE - JM100

PRODUCT NAME - Carpet Seaming Adhesive

CONTAINER SIZE - 500ml

TYPE - Synthetic rubber/resin adhesive

COVERAGE - 50 linear metres per 500ml container

OPEN TIME - Approximately 20 minutes

STORAGE - Store between temperatures of 5°C & 27°C

FLASH POINT - 17°C

SHELF LIFE - 12 months from the date of manufacturer

CLEANING - Remove surplus adhesive from carpet fibres immediately with a clean cloth and solvent based general purpose cleaner

Health and Safety Sheets available on request

morleys 
limited
stairnosings & flooring accessories

morleys limited, unit 2, higher walton mill,
higher walton, preston pr5 4dj

tel. 01772 626700

fax. 01772 627372

e-mail. sales@morleysltd.co.uk

website. www.morleysltd.co.uk



Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3

JM200 Peelbond Tackifier

A SOLVENT FREE acrylic, co-polymer, emulsion adhesive that can be applied by either trowel or roller. It dries to a permanently tacky finish. When laid into "dry" it provides a releasable bond, particularly for specific contract underlays developed for "double stick". When laid into "wet" it provides a permanent bond. It is non-staining, resistant to plasticiser migration, is suitable for use over normal underfloor heating systems and will withstand normal wet cleaning techniques.



USES

JM200 can be used to install the following:

Carpet Underlays: Specific contract grades developed for release bonding, eg. in double stick installations.

Carpets: With smooth backings including vinyl, polyurethane, gel-back and latex foam.

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g., moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

All parts of the installation should comply with the latest edition of the following British Standard Code of Practice: BS5325 The Installation of Textile Floorcoverings or BS8203 The Installation of Resilient Floorcoverings. Another useful source of reference is The C F A Guide to Contract Flooring.

Subfloors must be sound, smooth, clean, dry and free from any contamination which will affect adhesion. Relative humidity of cementitious subfloors should be 75% or less (when tested by the method described in BS8203). Direct to to earth bases must incorporate an effective damp proof membrane. Underfloor heating must be switched off 48 hours before and after the installation. Very absorbent surfaces should be primed with a suitable sealer

APPLICATION

For best results a minimum temperature of 18°C (65°F) should be maintained for the installation. FOR A RELEASABLE BOND THE ADHESIVE MUST BE COMPLETELY DRY BEFORE LAYING THE FLOORCOVERING:

Apply the adhesive evenly by roller or trowel (for Underlay: as specified by the manufacturer). For metal access floors always apply the adhesive by roller from a tray to avoid getting adhesive between the joints.

Any tools used should be cleaned with water immediately after use and whilst the adhesive is still wet.

Drying time will depend on temperature, humidity, subfloor porosity and trowel or roller used.

For releasable bond: allow the adhesive to dry completely before laying the floorcovering. After laying, apply a weighted roller or glider to ensure a good overall contact has been established and no air bubbles remain. (With some gel back and latex foam back floorcoverings, even dry laying can result in a permanent bond).

For permanent bond: lay the floorcovering into the adhesive whilst it is still wet or partially dry. For non-absorbent backings on a well sealed subfloor use the "double drop" technique. After laying, apply a weighted roller or glider to ensure a good overall contact. It may be necessary on some floorcoverings to roll a second time approximately 30 minutes later to ensure a strong bond is established.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given.

Ensure area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

TECHNICAL SPECIFICATION

PRODUCT CODE - JM200

PRODUCT NAME - Peelbond Tackifier

CONTAINER SIZE - 5 ltr & 15 ltr plastic buckets

TYPE - Acrylic Emulsion

COLOUR - Off White

VISCOSITY - Approx. 25,000 cps at 20°C - trowel or roller apply

COVERAGE - Between 4m² - 9m² per litre depending on trowel used & absorbency of sub floor

OPEN TIME - Wet application - approximately 40 mins depending on temperature, humidity, sub floor porosity & trowel used. Dry application - not

applicable, however dried surface of adhesive must be kept free from contamination until floor covering has been placed

STORAGE - Store between temperatures of 5°C and 30°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

CLEANING - Tools should be cleaned with water whilst the adhesive is wet. Use hot water or a solvent should the adhesive dry. Do not use on the skin

Health and Safety Sheets available on request

Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3

morleys

limited



JM300 Surface Tackifier

JM300 is a SOLVENT FREE modified acrylic emulsion adhesive. It is designed to provide a permanently tacky film for the positive holding of "loose-lay" carpet tiles but to enable them to be lifted and replaced easily when required.

The adhesive is easy to apply by either roller or brush. It is non-staining, resistant to plasticiser migration, suitable for use over normal underfloor heating systems and will withstand normal wet cleaning techniques.

USES

JM300 can be used to install the following: Carpet Tiles and fibrebonded/needlepunch Tiles backed with: PVC, bitumen/felt or non-woven fabric, pvc/glassfibre, hessian, APP and other polymer backings including polyurethane.

CAUTION: laying tiles before the adhesive has completely dried can result in a permanent bond being formed.

contamination which will affect adhesion. Relative humidity of cementitious subfloors should be 75% or less (when tested by method described in BS 8203). Direct to earth bases must incorporate an effective damp proof membrane. Underfloor heating must be switched off for 48 hours before and after the installation.

Very absorbent surfaces should be primed with a suitable sealer.

APPLICATION

For best results a minimum temperature of 18°C (65°F) should be maintained for the installation.

A brush or paint roller should be used to apply an even coating of the adhesive over the area to be covered. On metal access floors care must be taken to keep adhesive out of the joints between panels. This is best achieved by applying the adhesive from a tray. Any tools used should be cleaned with water immediately after use and whilst the adhesive is still wet. Allow the JM300 to dry to a clear tacky film before placing any of the tiles in position. This will take on average about 30 minutes. The time will vary with temperature, humidity, subfloor porosity and amount of adhesive applied. Airflow over the surface will reduce drying time.

CAUTION: Laying tiles before the adhesive has completely dried can result in a permanent bond being formed.

A bond will form immediately the tile is placed. When installation is complete a weighted roller or glider should be applied to ensure good overall contact has been established and no air bubbles remain.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given. Ensure area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.



SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g.. moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

All parts of the installation should comply with the latest edition of the following British Standard Code of Practice: BS5325 The Installation of Textile Floorcoverings or BS8203 The Installation of Resilient Floorcoverings. Another useful source of reference is The C F A Guide to Contract Flooring.

Subfloors must be sound, smooth, clean, dry and free from any

TECHNICAL SPECIFICATION

PRODUCT CODE - JM300

PRODUCT NAME - Surface Tackifier

CONTAINER SIZE - 5 ltr, & 25 ltr plastic jerry cans

TYPE - Acrylic Emulsion

COLOUR - Off White

VISCOSITY - Approx. 8,000 cps at 20°C - roller or brush apply

COVERAGE - Between 6m² - 7m² per litre depending on trowel used & absorbency of sub floor

OPEN TIME - Not applicable. However, dried

surface of adhesive must be kept free from contamination until flooring has been placed.

STORAGE - Store between temperatures of 5°C and 30°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

CLEANING - Tools should be cleaned with water whilst the adhesive is wet. Use hot water or a solvent should the adhesive dry. Do not use on the skin

Health and Safety Sheets available on request

morleys 
limited
stairmossings & flooring accessories

morleys limited, unit 2, higher walton mill,
higher walton, preston pr5 4dj

tel. 01772 626700

fax. 01772 627372

e-mail. sales@morleysltd.co.uk

website. www.morleysltd.co.uk



Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3

JM400 Multi-Purpose Adhesive

JM400 Multipurpose Adhesive is a superior performing high solids, water based floorcovering adhesive offering fast wet grab and strong final bond.

The adhesive is designed to suit a wide range of carpets. This includes carpets with hard to bond synthetic backings, such as latex/unitary or Action-Bac as well as Axminsters and jute hessian backed.

The adhesive is easy to spread, is suitable for use over normal underfloor heating installations, and will withstand normal wet cleaning techniques.



USES

JM400 can be used to install the following:

Carpets:

Jute secondary backed, Axminster, Wilton, synthetic secondary backed, needlepunch/fibrebonded, latex/unitary backed, Action-Bac, latex foam, gel back, felt back and bitumen/non woven backed. For carpets recommended for "double stick" systems the JM400 is an ideal permanent bond adhesive.

Do NOT use for:

Urethane backed carpets

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g., moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

All parts of the installation should comply with the latest edition of the following British Standard Code of Practice: BS5325 The Installation of Textile Floorcoverings or BS8203 The Installation of Resilient Floorcoverings. Another useful source of reference is The CFA Guide to Contract Flooring.

Subfloors should be sound, smooth, clean, dry and free from any

contamination which will affect adhesion. Relative humidity of cementitious subfloors should be 75% or less (when tested by the method described in BS8203). Direct to earth bases must incorporate an effective damp proof membrane. Underfloor heating must be switched off for 48 hours before and after the installation. Very absorbent surfaces should be primed with a suitable sealer.

APPLICATION

For best results a minimum temperature of 18°C (65°F) should be maintained for the installation.

An appropriate V notched trowel should be used to apply the adhesive evenly. For most carpets a 2.0mm x 6.0mm or MT-B1 will be suitable. However, for rough backed or ribbed carpet a 3.0mm x 6.0mm or MT-B2 trowel is recommended and for smooth floorcoverings a 1.5mm x 5.0mm or MT-A2 should be used. Trowels should be cleaned after use with water whilst the adhesive is still wet. Apply adhesive evenly to an area of such size that the floorcoverings can be laid whilst the adhesive is receptive and gives good transfer (usually whilst the adhesive is still wet). *When installing an impervious floorcovering onto a well sealed subfloor allow the adhesive to develop a slight tack or employ a "double drop" technique to reduce the waiting time before laying.*

Unless the floorcovering manufacturer recommends otherwise the entire installation should be rolled or weighted glider applied in both directions immediately the installation is complete to remove any trapped air and ensure good adhesive transfer. It may be necessary on some floorcoverings to roll a second time, approximately 1 hour later, to ensure a strong bond is established.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given. Ensure area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.

TECHNICAL SPECIFICATION

PRODUCT CODE - JM400

PRODUCT NAME - Multi Purpose Adhesive

CONTAINER SIZE - 5 ltr & 15 ltr plastic buckets

TYPE - Rubber/Resin Emulsion

COLOUR - Off White

VISCOSITY - 70,000 - 90,000cps at 20°C

COVERAGE - Approximately 3m² per litre depending on trowel used and absorbency of sub floor

OPEN TIME - Between 20-40 mins, depending on temperature, humidity, sub floor porosity & trowel used

STORAGE - Store between temperatures of 5°C & 30°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

CLEANING - Tools should be cleaned with water whilst the adhesive is wet. Use hot water or a solvent should the adhesive dry. Do not use on the skin

Health and Safety Sheets available on request

Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3

morleys

limited



JM500 Acrylic Adhesive

JM500 is a SOLVENT FREE acrylic emulsion based adhesive. This easy to spread adhesive, with long open time, provides early tack and minimum slip, quickly building to a strong permanent bond. It is non-staining, has excellent resistance to plasticiser migration and is suitable for use over normal underfloor heating installations.

USES

JM500 can be used to install the following:

Hard/Resilient Floorcoverings:

Vinyls: Sheet, tiles, cushion and other vinyl backed floorcoverings including mineral felt backed vinyls.

Carpets: PVC backed, polyurethane foam backed and many other carpets and needlepunch / fibrebonded carpets where a solvent free system is specified.

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g.. moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

All parts of the installation should comply with the latest edition of the following British Standard Code of Practice: BS8203 The Installation of Resilient Floorcoverings or BS5325 The Installation of Textile Floorcoverings. Another useful source of reference is The CFA Guide to Contract Flooring.

Subfloors must be sound, smooth, clean, dry and free from any contamination which will affect adhesion. Relative humidity of cementitious subfloors should be 75% or less (when tested by method described in BS 8203). Direct to earth bases must incorporate an effective damp proof membrane. Underfloor heating must be switched off for 48 hours before and after the installation.

Very absorbent surfaces should be primed with a suitable sealer.

APPLICATION

For best results a minimum temperature of 18°C (65°F) should be maintained for the installation. An appropriate V notched trowel should be used to apply the adhesive evenly. For vinyls and other smooth backed floorcoverings a 1.5mm x 5.0mm, MT-A1 or MT-A2 is recommended whilst a larger trowel should be selected for floorcoverings with a more profiled back.

Trowels should be cleaned after use with water whilst the adhesive is still wet.

Apply the adhesive evenly to an area of such a size that the floorcovering can be laid whilst the adhesive is receptive and gives good transfer.

On absorbent surfaces lay the floorcovering immediately or in the case of tiles after 10-15 minutes (this reduces the slip). *On non-absorbent surfaces allow the adhesive to develop a tack or, for sheet goods, employ a "double drop" technique to reduce the waiting time before laying.*

To reduce the effect of shadowing on some vinyls, it is recommended that the adhesive is smoothed out whilst wet with a paint roller that has been pre-wetted with adhesive. Once installation area is laid, roll immediately in two directions (at right angles to each other) with a 68kg roller (on carpets use a weighted glider). This is to remove any trapped air and ensure good all over adhesive contact. A second rolling (or gliding) is recommended approximately 1 hour later to ensure a strong bond is established.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given.

Ensure area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.

morleys 
limited
stairnosings & flooring accessories

morleys limited, unit 2, higher walton mill,
higher walton, preston pr5 4dj

tel. 01772 626700

fax. 01772 627372

e-mail. sales@morleysltd.co.uk

website. www.morleysltd.co.uk

TECHNICAL SPECIFICATION

PRODUCT CODE - JM500

PRODUCT NAME - Acrylic Adhesive

CONTAINER SIZE - 5ltr & 15ltr Plastic Buckets

TYPE - Acrylic Emulsion

COLOUR - Off-white

VISCOSITY - Approx 45,000 cps at 20°C - trowel apply

COVERAGE - Between 3.5m² - 5m² per litre depending on trowel used and absorbancy of subfloor

OPEN TIME - Up to 1 hour depending on

temperature, humidity, subfloor porosity and trowel used

STORAGE - Store between temperatures of 5°C and 30°C

SHELF LIFE - 12 months in unopened

containers, stored in recommended conditions

CLEANING - Tools should be cleaned with water whilst the adhesive is wet. Use hot water or a solvent should the adhesive dry. Do not use on the skin

Health and Safety Sheets available on request



Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3

JM600 Latex Adhesive

A SOLVENT FREE natural rubber latex adhesive used as a general purpose carpet adhesive.

USES

Its main use is for the permanent bonding of edges and seams of traditional carpets to prevent fibre loss. It is used with hessian seaming tape (Morley product code H5) for cold seaming of carpets. It can be used with jute hessian backed carpet for "repair" of permanent bonding to subfloor.

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g.. moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

All parts of the installation should comply with the latest edition of BS 5325 The Installation of Textile Floorings. Another useful source of reference is The C F A Guide to Contract Flooring.

APPLICATION

For best results a minimum temperature of 18°C (65°F) should be maintained for the installation.

Edge Sealing: apply the adhesive by brush or applicator to the edge of the carpet, having first removed any loose fibres. Allow the adhesive to fully dry before continuing with the installation.

Seaming: make sure both edges of the carpet are cleanly cut and free from loose fibres; apply an even coat of JM600 to the back of the carpet and the seaming tape (Morley product code H5). Allow the adhesive to partially dry before pressing the two coated surfaces firmly together using a hand roller (Morley product code MT-100 or MT-106-SM carpet seam roller).

Caution: Do not stretch the carpet until the adhesive is completely dry. It could result in the seam opening up.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given.

Ensure area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.



WHITE LID

TECHNICAL SPECIFICATION

PRODUCT CODE - JM600

PRODUCT NAME - Latex Adhesive

CONTAINER SIZE - 5 ltr plastic jerry can

TYPE - Natural Rubber Latex

COLOUR - Off White

VISCOSITY - Approx. 4500 cps at 20°C - brush or applicator apply

COVERAGE - N/A

OPEN TIME - Approximately 20 minutes depending on temperature, humidity, sub floor porosity and trowel used

STORAGE - Store between temperatures of 5°C and 30°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

CLEANING - Tools should be cleaned with water whilst the adhesive is wet. Use hot water or a solvent should the adhesive dry. Do not use on the skin

Health and Safety Sheets available on request

morleys limited
stairnosings & flooring accessories

morleys limited, unit 2, higher walton mill,
higher walton, preston pr5 4dj

tel. 01772 626700

fax. 01772 627372

e-mail. sales@morleysltd.co.uk

website. www.morleysltd.co.uk


Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3

morleys

limited



JM700 Premium Pressure Sensitive Adhesive



JM700 is a SOLVENT FREE pressure sensitive acrylic adhesive that is easily applied either by trowel, roller or brush. It dries quickly to form a strong pressure sensitive adhesive for resilient floorcoverings. The adhesive is non-staining, has excellent resistance to plasticiser migration and is suitable for use over normal underfloor heating systems.

USES

JM700 can be used to install the following: PVC, vinyl sheet, vinyl tile, vinyl cushion, other vinyl backed floorcoverings including textile felt backed vinyls. Carpets with backings of PVC, polyurethane foam, gel (including impervious), and felt backed carpets. JM700 could also be suitable for other

floorcoverings including some cork, linoleum tiles and rubber. If there is any doubt over the suitability of the adhesive for any application the installer should carry out tests to prove suitability or contact our Technical Department.

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g. moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation. Please contact office for technical information.**

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

All parts of the installation should comply with the latest edition of the following British Standard Code of Practice: BS8203 The Installation of Resilient Floorcoverings or BS5325 The Installation of Textile Floorcoverings. Another useful source of reference is The CFA Guide to Contract Flooring.

Subfloors must be sound, smooth, clean, dry and free from any contamination that will affect adhesion. Relative humidity of cementitious subfloors should be 75% or less (when tested by method described in BS8203). Direct to earth bases must incorporate an effective damp proof membrane. Underfloor heating must be switched off for 48 hours before and after the installation. Very absorbent surfaces should be primed with a suitable sealer.

APPLICATION

For best results a minimum temperature of 18°C (65°F) should be

maintained for the installation with a floor temperature of at least 10°C (50°F). An appropriate V notched trowel should be used to apply the adhesive evenly. For vinyls and other smooth backed floorcoverings a 1.5mm x 5.00mm or MT-A1 or MT-A2 trowel is recommended. To reduce the effect of shadowing on some vinyls, it is recommended that the adhesive is smoothed out whilst wet with a paint roller that has been pre-wetted with adhesive. For floorcoverings with a more profiled back a larger trowel should be selected. Clean off any adhesive contamination with water whilst the adhesive is still wet.

This versatile adhesive can now be used as a wet-bond, pressure sensitive or contact adhesive onto absorbent substrates and as a pressure sensitive or contact adhesive onto non-absorbent substrates.

For wet-bond: Allow an open time of 5 to 20 minutes; lay the floorcovering and roll it with a 68kg roller in two directions within 30 minutes and again within 2 hours.

For pressure sensitive: Allow an open time to when the adhesive has developed a slight tack to the touch. This is usually between 20 and 40 minutes. The open time can be reduced by, either smoothing out the wet adhesive with a pre-wetted roller or employing a "double drop" technique. After the floorcovering is placed, roll it with a 68kg roller in two directions and again within 2 hours.

For contact adhesion: Always smooth out the wet adhesive with a pre-wetted roller or use the "double drop" technique and then allow the adhesive to dry completely. After the floorcovering is placed, roll it in two directions with a 68kg roller.

Note: The application of a heavy roller onto the completed installation will always increase the bond strength with this adhesive.

COVERAGE

Between 4m² - 9m² per litre depending on application method and absorbency of subfloor.

STORAGE

Store at a temperature between 5°C (41°F) and 30°C (86°F)

SHELF LIFE

12 months in unopened containers, stored in recommended conditions.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given. Ensure the area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.

morleys 
limited
stairmossings & flooring accessories

morleys limited, unit 2, higher walton mill,
higher walton, preston pr5 4dj

tel. 01772 626700

fax. 01772 627372

e-mail. sales@morleysltd.co.uk

website. www.morleysltd.co.uk

TECHNICAL SPECIFICATION

PRODUCT CODE - JM700

PRODUCT NAME - Premium Pressure Sensitive Adhesive

CONTAINER SIZE - 5ltr & 15ltr Plastic Buckets

TYPE - Acrylic Emulsion

COLOUR - Off White

VISCOSITY - 30,000- 40,000cps at 20°C, trowel apply

COVERAGE - Between 4m² - 9m² per litre depending on trowel used and absorbency of subfloor

OPEN TIME - All times are dependent on temperature, humidity, subfloor porosity and

application method Wet application- up to 20minutes Pressure Sensitive application- 20 to 40 minutes Contact- Up to 24 hours after drying if kept free of contamination

STORAGE - Store between temperatures of 5°C and 30°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

CLEANING - Tools should be cleaned with water whilst the adhesive is wet. Use hot water or solvent should the adhesive dry. Do not use solvent on skin

Health and Safety Sheets available on request



Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3

JM800 Spray-On Contact Adhesive System

JM800 Spray-on Contact Adhesive is a versatile, high quality contact adhesive that is sprayed onto the surfaces, thus saving the floor layer hours. Tests prove up to three times faster application. JM800 is fast drying with a long open time, excellent coverage and no wastage. Suitable for most vinyls, carpets, and PVC flooring accessories.

USES

JM800 can be used to install the following:
PVC Skirtings, cappings and Coveformers, vinyl sheet, vinyl backed floorcoverings, wood, fabric, cardboard, polythene and decorative laminates.

Carpets: Jute secondary backed, synthetic secondary backed, needlepunched/fibrebonded, latex/unitary backed, latex foam, gel backed, and felt backed.

Note: Always test a small sample of material to be bonded, the test conditions must replicate the site conditions e.g. ambient temperatures, moisture content, before starting the installation. Some vinyls for example, contain large amounts of plasticiser, which can soften and dissolve the bond over time.

With vertical applications there are certain paints/primers used, which can impair the performance of JM800. We recommend you consult our technical department before application.

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plywood, flooring grade chipboard, hardboard and wood.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g., moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

PREPARATION

All parts of the installation should comply with the latest edition of the following British Standard Code of Practice: BS5325 The Installation of Resilient Flooring or BS5325 The Installation of Textile Floorcoverings. Another useful source of reference is The CFA Guide to Contract Flooring. Subfloors must be sound, smooth, clean, dry and free from any contamination which will affect the adhesion. Relative humidity of cementations subfloors should be 75% or less (when tested by the method described in BS8203). Direct to earth bases must incorporate an effective damp proof membrane. Very absorbent surfaces should be primed with a suitable sealer. Note: This adhesive is not suitable for underfloor heating installations.

APPLICATION

1. When connecting the hose to the gun and the canister for the first time please ensure a spanner is used to tighten the nuts to avoid any leakage of adhesive. Prime the gun and hose with the spray tip nozzle removed, this is achieved by pulling back the trigger on the spray gun until all the air is expelled from the gun and hose and the adhesive is flowing out of the spray gun. Failure to prime the a new gun and hose could result in a blocked spray tip nozzle. Replace the the nozzle

(vertical slot for spraying left to right, horizontal for spraying up and down) then tighten the nozzle housing nut.

2. Once the hose has been connected to the canister, always keep the valve on the canister open and the hose and spray gun pressurised at all times. **Do not disconnect hose from empty canister until you are ready to connect to new full canister**, this avoids adhesive drying in the hose and spray gun.

3. Always test a small sample of material to be bonded before starting installation. Some vinyls, for example, contain large amounts of plasticiser, which soften and dissolve the bond over time.

4. Mark area to be sprayed. If necessary use masking tape to define the area and avoid any over spray onto newly decorated walls.

5. Use JM800 in a well-ventilated area.

6. For best results apply at room temperature. If this is not possible in severe weather condition immerse the canister in warm water to raise the the canister temperature, this will avoid any adhesive separation.

7. Hold the tip of the spray gun at 150mm to 300mm away from the surface and maintain a content 90° angle. Do not tilt the spray angle. Do not allow the adhesive to puddle due to excessive spraying.

8. Apply adhesive uniformly in a web pattern to both surfaces. One surface should be sprayed vertically and the other horizontally, where possible, to ensure a secure bond. Coverage should be 80% to 100%.

9. Allow the adhesive to dry completely before bonding both surfaces; this should take 3 to 5 minutes depending on the temperature and humidity. Both surfaces should be touch dry.

10. Place the materials accurately into position and press firmly to exclude any air and to ensure overall contact, and roll the floor area with a 68kg roller.

11. Laminate and wood products may expand and contract depending on temperature and humidity. When bonding these materials, it is recommended they are stored at room temperature for at least 48 hours prior to applying adhesive and assembly.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet.

Ensure area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.



TECHNICAL SPECIFICATION

PRODUCT CODE - JM800

PRODUCT NAME - Spray-On Contact Adhesive

CONTAINER SIZE - 17kg and 500ml

TYPE - A blend of synthetic rubbers and resins

COLOUR - Clear and red

COVERAGE - Between 150m² and 200m² per 17kg canister, between 4m² and 5m² per 500ml can. Drying time 3 to 5 minutes

OPEN TIME - 24 hours

STORAGE - Store between temperatures of 5°C & 23°C

SHELF LIFE - 12 months from the date of manufacture

CLEANING - Any over spray can be removed by rubbing whilst the adhesive is still fresh, or use a mild solvent cleaner on a cloth to soften the JM800 once the adhesive fully dries.

Health and Safety Sheets available on request

Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3



JM900 Entrance Matting Adhesive

JM900 is a specially formulated SOLVENT FREE acrylic copolymer emulsion adhesive. This easy to spread adhesive is designed for the permanent bonding of Morley Entrance Matting. The adhesive dries to form a strong bond that is also pressure sensitive i.e. the more you roll it the stronger it becomes. The adhesive is non-staining, has excellent resistance to plasticiser migration and is suitable for use over normal underfloor heating installations.

This adhesive is NOT recommended for use in wet areas.



USES

JM900 is recommended for permanent bonding the range of Morley Entrance Matting

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g.. moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

All parts of the installation should comply with the latest edition of the following British Standard Code of Practice: BS8203 The Installation of Resilient Floorcoverings or BS5325 The Installation of Textile Floorcoverings. Another useful source of reference is The CFA Guide to Contract Flooring.

Subfloors must be sound, smooth, clean, dry and free from any contamination that will affect adhesion. Relative humidity of cementitious subfloors should be 75% or less (when tested by method described in BS8203). Direct to earth bases must

incorporate an effective damp proof membrane. Underfloor heating must be switched off for 48 hours before and after the installation. Very absorbent surfaces should be primed with a suitable sealer.

APPLICATION

For best results a minimum air temperature of 18°C (65°F) and a floor temperature of 10°C (50°F) should be maintained for the installation. An appropriate V notched trowel should be used to apply the adhesive evenly.

Any tools should be cleaned after use with water whilst the adhesive is still wet.

For profiled and porous backings: a 2.0mm x 6.0mm or MT-B1 V notched trowel is recommended. On absorbent surfaces the matting can be laid immediately or for faster bond development allow the adhesive to develop a slight tack before laying.

For vinyl and smooth backings: a 1.5mm x 5.0mm or MT-A2 V notched trowel is recommended. The adhesive should be allowed to develop a slight tack before placing the matting. To reduce waiting time before laying, the "double drop" method can be employed. When the installation is laid, press the matting from the centre outwards to exclude any bubbles and then roll with a 68kg roller in two directions. A second heavy roller application after about 1 hour is recommended to ensure a strong bond is established.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given. Ensure the area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.

TECHNICAL SPECIFICATION

PRODUCT CODE - JM900

PRODUCT NAME - Entrance Matting Adhesive

CONTAINER SIZE - 5ltr Plastic Buckets

TYPE - Acrylic Emulsion

COLOUR - Off-white

VISCOSITY - Approx 30,000cps at 20°C

COVERAGE - Between 3m²- 4.5m² per litre depending on trowel used and absorbency of subfloor

OPEN TIME - Up to 40 minutes for wet or "slight tack" application depending on temperature, humidity, subfloor porosity and trowel used

STORAGE - Store between temperatures of 5°C and 30°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

CLEANING - Tools should be cleaned with water whilst the adhesive is wet. Use hot soapy water or solvent if the adhesive is dry. Do not use solvent on skin

Health and Safety Sheets available on request

morleys 
limited
stairmossings & flooring accessories

morleys limited, unit 2, higher walton mill,
higher walton, preston pr5 4dj

tel. 01772 626700

fax. 01772 627372

e-mail. sales@morleysltd.co.uk

website. www.morleysltd.co.uk



Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3

JM1000

Water Based Universal Primer

JM1000 is a water based primer specially formulated to aide adhesion on absorbent surfaces. JM1000 is coloured green for easy identification.



USES

JM1000 is recommended for priming absorbent surfaces, such as sand/cement, concrete, plywood, screeds and some non-absorbent surfaces such as ceramic and quarry tiles and power floated concrete, prior to the installation of Peel and Stick Stairnosing. JM1000 can be used as a primer for dusty absorbent surfaces, to achieve greater adhesive coverage and prevent the adhesive drying prematurely.

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g.. moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this primer. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

All parts of the installation should comply with the latest edition of the following British Standard Code of Practice: BS8203 The Installation of

Resilient Floorcoverings or BS5325 The Installation of Textile Floorcoverings. Another useful source of reference is The CFA Guide to Contract Flooring.

Subfloors must be sound, smooth, clean, dry and free from any contamination which will affect adhesion. Relative humidity of cementitious subfloors should be 75% or less (when tested by method described in BS 8203). Direct to earth bases must incorporate an effective damp proof membrane. Underfloor heating must be switched off for 48 hours before and after the installation.

Very absorbent surfaces should be primed with a suitable sealer.

APPLICATION

Shake well before use. Do not dilute.

Peel and Stick Installations: Apply undiluted JM1000 with a paint brush onto the surface of the step. Allow the JM1000 to dry totally before installing Peel and Stick.

Priming: Apply undiluted JM1000 with a paint roller or sweeping brush over the entire floor surface. Allow to dry before applying any adhesive.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given.

Ensure area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.

TECHNICAL SPECIFICATION

PRODUCT CODE - JM1000

PRODUCT NAME - Universal Primer

CONTAINER SIZE - 500ml, 1 ltr Plastic Bottles & 5 ltr Plastic Jerry cans

TYPE - Co-polymer Dispersion

COLOUR - Green

VISCOSITY - As Water

COVERAGE - Between 10m² - 12m² per litre depending on absorbency of subfloor

OPEN TIME - All times are dependent temperature, humidity and subfloor porosity and application method. Approximately 10 to 20 mins

STORAGE - Store between temperatures of 5°C and 30°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

CLEANING - Tools should be cleaned with water whilst the adhesive is wet. Use hot water or solvent should the adhesive dry. Do not use solvent on skin

Health and Safety Sheets available on request

Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3



A1 Heavy Duty Spray Adhesive

The Morley Heavy Duty Spray is truly heavy duty. It is a multi-functional adhesive used for the perimeter fixing of most types of carpets, tiles, underlays & associated products. It is CFC free and has an adjustable nozzle, allowing different thickness of band to be sprayed.



USES

It is used to fix foam backed carpets, carpet tiles, carpet and foam underlays, felt textiles and fabrics.

APPLICATION

Spray the adhesive evenly from a distance of 10-20cms. For a strong bond, spray a number of light coats on both surfaces. For a lighter bond apply to one surface only. Allow approx. 1-5 mins for the adhesive to become tacky, then press surfaces together firmly, working outwards from the centre to adhere a good bond. Excess adhesive can be removed with white spirit.

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g.. moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

Ensure that surfaces are clean, dry and dirt free. Shake can well before use.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given. Ensure area of use is well ventilated. Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves. In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help. If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.

TECHNICAL SPECIFICATION

PRODUCT CODE - A1

PRODUCT NAME - Heavy Duty Spray Adhesive

CONTAINER SIZE - 500ml aerosol can

OPEN TIME - 1-5 mins depending on temperature, humidity and sub floor porosity

STORAGE - Store between temperatures of 5°C and 25°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

CLEANING - Overspray can be removed with a small amount of white spirit. Always test before going ahead

Health and Safety Sheets available on request

morleys 
limited
stairnosings & flooring accessories

morleys limited, unit 2, higher walton mill,
higher walton, preston pr5 4dj

tel. 01772 626700

fax. 01772 627372

e-mail. sales@morleysltd.co.uk

website. www.morleysltd.co.uk



Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3

A2 Heavy Duty Gripper Adhesive

This gunnable adhesive has a setting time of approximately 8 hours, depending on site conditions.

USES

It is most commonly used for the fixing of carpet grippers, trims and stairnosings. It can also be used to fix plastic & wooden skirtings, batons, boards and panels. It also can be used as a gap filler.

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g., moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

All parts of the installation should comply with the latest edition of the following British Standard Code of Practice: BS5325 The Installation of Textile Floorcoverings of BS8203 The Installation of Resilient Floorcoverings. Another useful source of reference is The CFA Guide to Contract Flooring.

Subfloors must be sound, smooth, clean, dry and free from any contamination which will affect adhesion. Relative humidity of cementitious subfloors should be 75% or less (when tested by method described in BS 8203). Direct to earth bases must

incorporate an effective damp proof membrane.

Underfloor heating must be switched off for 48 hours before and after the installation.

Very absorbent surfaces should be primed with a suitable sealer.

APPLICATION

Cut off the first 10-15cm of nozzle, load cartridge into a skeleton gun, puncture cartridge through the nozzle

end, apply adhesive in 6mm beads. Press into position and ensure a good transfer of adhesive has taken place. For a stronger initial bond, press the item into position, then pull it away immediately. Allow to dry apart for 10-20 mins before pressing finally into position.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given.

Ensure area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.



TECHNICAL SPECIFICATION

PRODUCT CODE - A2

PRODUCT NAME - Gripper Adhesive

CONTAINER SIZE - 380ml cartridge

TYPE - Synthetic rubber / resin adhesive

COLOUR - Beige

COVERAGE - 15 linear metres depending on width of bead and speed of application

OPEN TIME - Approximately 30 minutes depending on temperature, humidity, sub floor porosity

CURING TIME - Approximately 8 hours

STORAGE - Store between temperatures of 5°C and 25°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

Health and Safety Sheets available on request

Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3



A3 Heavy Duty Vinyl Spray Adhesive

The Morley Heavy Duty Vinyl Adhesive is for the perimeter fixing of all types of vinyl flooring as it is plasticizer migration resistant. It is also CFC free.



USES

It is used to fix all types of vinyl floorings, including vinyl backed carpets and tiles.

APPLICATION

Spray the adhesive evenly from a distance of 10-20cms. For a strong bond, spray a number of light coats on both surfaces. For a lighter bond apply to one surface only. Allow 3-5 mins for the adhesive to become tacky, then press surfaces together firmly, working outwards from the centre to adhere a good bond. Excess adhesive can be removed with white spirit.

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given. Ensure area of use is well ventilated. Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves. In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help. If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.

underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated, e.g.. moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

Ensure that surfaces are clean, dry and dirt free. Shake can well before use.



morleys limited, unit 2, higher walton mill,
higher walton, preston pr5 4dj

tel. 01772 626700

fax. 01772 627372

e-mail. sales@morleysltd.co.uk

website. www.morleysltd.co.uk

TECHNICAL SPECIFICATION

PRODUCT CODE - A3

PRODUCT NAME - Heavy Duty Vinyl Spray Adhesive

CONTAINER SIZE - 500ml aerosol can

OPEN TIME - 3-5 mins depending on temperature, humidity, sub floor porosity & trowel used

STORAGE - Store between temperatures of 5°C and 25°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

CLEANING - Overspray can be removed with a small amount of white spirit. Always test before going ahead

Health and Safety Sheets available on request

Uniclass L5391:L673	EPIC E4:F73
CI/SfB (43)	Yt3

A17 Fast Setting Gripper Adhesive

This gunnable adhesive has an extremely fast setting time, allowing jobs to be finished in a fraction of the time when compared to traditional methods.

USES

It is most commonly used for the fixing of carpet grippers, trims and stairnosings. It can also be used to fix plastic and wooded skirtings, batons and panels.

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types floor/wall boards in use that have been treated , e.g.. moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation.**

Please contact office for technical information.

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. If this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

All parts of the installation should comply with the latest edition of the following British Standard Code of Practice: BS5325 The Installation of Textile Floorcoverings of BS8203 The Installation of Resilient Floorcoverings. Another useful source of reference is The CFA Guide to Contract Flooring.

Subfloors must be sound, smooth, clean, dry and free from any contamination which will affect adhesion. Relative humidity of cementitious subfloors should be 75% or less (when tested by

method described in BS 8203). Direct to earth bases must incorporate an effective damp proof membrane. Underfloor heating must be switched off for 48 hours before and after the installation.

Very absorbent surfaces should be primed with JM1000 Universal Primer.

APPLICATION

Cut off the top of the cartridge and attach the nozzle. Load cartridge into a skeleton gun and apply a thin bead of adhesive. **Do not**

cut the nozzle. Press the product into the adhesive immediately and allow to set. Curing time will be anything up to 1 hour on absorbent surfaces at 15°C. Cooler temperatures will prolong the curing time. Non absorbent surfaces will prolong the curing time.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given. Ensure area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.



TECHNICAL SPECIFICATION

PRODUCT CODE - A17

PRODUCT NAME - Fast Setting Gripper Adhesive

CONTAINER SIZE - 310ml

TYPE - Moisture curing polyurethane

COLOUR - Off white

COVERAGE - 30-40 linear metres depending on speed of application

OPEN TIME - Up to 5 minutes depending on temperature, humidity, subfloor porosity etc

STORAGE - Store between temperatures of 5°C and 25°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

Health and Safety Sheets available on request

Recommended User Guide

The information in this guide has been prepared to assist specifiers and installers select the most suitable adhesive for their installation. As floorcovering manufacturers, in their pursuit of improvements, introduce changes to their products and ranges, it is not possible to take account of all these changes. In any installation, site conditions can vary, and therefore the user must ensure the suitability of our products by enquiry or the carrying out of appropriate tests.

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

ADAM CARPETS LTD • Tel 01562 829966 • Fax 01562 751471

All Qualities	Unitary	JM400	JM200	JM800
Blenheim Court	Jute Hessian	JM400	JM200	JM800
Blenheim Grange	Jute Hessian	JM400	JM200	JM800
Blenheim House	Jute Hessian	JM400	JM200	JM800
Blenheim Palace	Jute Hessian	JM400	JM200	JM800
Castlemead Twist	Synthetic	JM400	JM200	JM800
China Garden	Jute Hessian	JM400	JM200	JM800
Fine Upland Twist	Synthetic	JM400	JM200	JM800
Fine Worcester Twist	Synthetic	JM400	JM200	JM800
Florentine Collection	Synthetic	JM400	JM200	JM800
Inspirations	Synthetic	JM400	JM200	JM800
Kasbah Twist	Synthetic	JM400	JM200	JM800
Natural Perceptions	Synthetic	JM400	-	JM800
Peacock Garden	Synthetic	JM400	JM200	JM800
Sylvan Shadows	Synthetic	JM400	JM200	JM800
Tea Garden	Synthetic	JM400	JM200	JM800
Woodstock	Synthetic	JM400	JM200	JM800
Woodstock Classic	Synthetic	JM400	-	JM800
Woodstock Range Tiles	P V C	-	JM300	-
Woodstock Range Tiles	Bitumen / Felt	JM400	JM300	-
Woodstock Studio	Jute Hessian	JM400	JM200	JM800

THE ALTERNATIVE FLOORING COMPANY • Tel 01264 335111 • Fax 01264 336445

Coir Range	Latex	JM400	-	JM800
Jute Range	Latex	JM400	-	JM800
Mountain Grass Range	Latex	JM400	-	JM800
Seagrass	Latex	JM400	-	JM800
Sisal Range	Latex	JM400	-	JM800
Wool Range	Jute Hessian	JM400	-	JM800

ALTRO FLOORS LTD • Tel 01462 707700 • Fax 01462 707500

Altro Atlas 40	P V C	JM500, JM700	-	JM800
Altro Classic 25	P V C	JM500, JM700	-	JM800
Altro Designer 25	P V C	JM500, JM700	-	JM800
Altro Impressionist II	P V C	JM500, JM700	-	JM800
Altro Imprint	P V C	JM500, JM700	-	JM800
Altro Marine 20	P V C	-	-	JM800
Altro Maxis 25	P V C	JM500, JM700	-	JM800
Altro Maxis Suprema	P V C	JM500, JM700	-	JM800
Altro Mondo Sportflex	Rubber	-	-	JM800
Altro Mondoflex	Rubber	-	-	JM800
Altro Mondofutura 2mm	Rubber	-	-	JM800
Altro Mondopave MPE 2.5mm	Rubber	-	-	JM800
Altro Mondopave MPE 4.0mm	Rubber	-	-	JM800
Altro Mondosport HP	P V C Foam	JM500, JM700	-	JM800
Altro Ramflex	Rubber	-	-	JM800
Altro Smooth Chrysalis	P V C	JM500, JM700	-	JM800
Altro Smooth Ethos/Moods	P V C	JM500, JM700	-	JM800
Altro Smooth Intrinsic	P V C	JM500, JM700	-	JM800
Altro Smooth Synthesis	P V C	JM500, JM700	-	JM800
Altro Stronghold 30	P V C	-	-	JM800
Altro Timber Natural	P V C	JM500, JM700	-	JM800
Altro Walkway 20	P V C	JM500, JM700	-	JM800

ALVIN MORRIS LTD (MERCADO CARPETS) • Tel 0113 3802900 • Fax 0113 3802828

Absorber	P V C	JM900	-	-
Bavik	Gel Foam	JM400, JM200	-	JM800
Belgrove	Gel Foam	JM400, JM200	JM200	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Campus X-treme	Impervious Gel	JM400, JM200	-	JM800
Canyon	Rubber Waffle	JM400, JM700	-	JM800
Castle	Impervious Gel	JM400, JM200	-	JM800
Ceasar	Gel Foam	JM400, JM200	-	JM800
Cheetah	Gel Foam	JM400, JM200	-	JM800
Commerce Gel Rib	Gel Foam	JM400, JM200	-	JM800
Commerce Gel Rib	Resin	JM400	-	JM800
Commerce Gel Velour	Gel Foam	JM400, JM200	-	JM800
Commerce Gel Velour	Resin	JM400	-	JM800
Commerce Entrance	Gel Foam	JM400, JM200	-	JM800
Commerce Resin Rib	Gel Foam	JM400, JM200	-	JM800
Commerce Tile Rib	Bitumen Felt	-	JM300	-
Commerce Tile Velour	Bitumen Felt	-	JM300	-
Commercial Cord	Gel Foam	JM400, JM200	-	JM800
Dorian	Gel Foam	JM400, JM200	-	JM800
Dread Lock	Gel Foam	JM400, JM200	-	JM800
Everest	Impervious Gel	JM400, JM200	-	JM800
Explorer Rib	Gel Foam	JM400, JM200	-	JM800
Foyer	Gel Foam	JM400, JM200	-	JM800
Grimefighter 2006	P V C	JM900	-	-
Healthcare Classic	Gel Foam	JM400, JM200	-	JM800
Healthcare Design	Impervious Gel	JM400, JM200	-	JM800
Healthcare Select	Gel Foam	JM400, JM200	-	JM800
Healthcare Select	Gel Foam	JM400, JM200	-	JM800
Highguard	FR Gel Foam	JM400	-	JM800
Hercules	Gel Foam	JM400, JM200	-	JM800
Jaguar	Impervious Gel	JM400, JM200	-	JM800
Loby	Gel Foam	JM400, JM200	-	JM800
Magic Velour	Gel Foam	JM400, JM200	-	JM800
Marina	Gel Foam	JM400, JM200	-	JM800
Mars	Impervious Gel	JM400, JM200	-	JM800
Miami	Gel Foam	JM400, JM200	-	JM800
Micra	Gel Foam	JM400, JM200	-	JM800
New Derby	Gel Foam	JM400, JM200	-	JM800
Office Velour	Gel Foam	JM400, JM200	-	JM800
Olymus	Impervious Gel	JM400, JM200	-	JM800
Prisma (Supreme)	Gel Back	JM400, JM200	-	JM800
Puma	Gel Foam	JM400, JM200	-	JM800
Puma (Supreme)	Gel Foam	JM400, JM200	-	JM800
Quadrille	Secondary	JM400, JM200	JM200	JM800
Rally	Gel Foam	JM400, JM200	-	JM800
Regatta	Gel Foam	JM400, JM200	-	JM800
Rodeo	Gel Foam	JM400, JM200	-	JM800
Sapphire	Gel Foam	JM400, JM200	-	JM800
Samson Rib	Rubber Waffle	JM400, JM700	-	JM800
Samson Velour	Rubber Waffle	JM400, JM700	-	JM800
Saracen	Impervious Gel	JM400, JM200	-	JM800
Scala Tonals	Gel Foam	JM400, JM200	-	JM800
Soilguard	Gel Foam	JM400, JM200	-	JM800
Stainaway Conquest	Gel Foam	JM400, JM200	-	JM800
Stainfree Conqueror	Gel Foam	JM400, JM200	-	JM800
Step Ahead	P V C	JM900	-	-
Warrior Gel	Gel Foam	JM400, JM200	-	JM800
York	Gel Foam	JM400, JM200	-	JM800

AML CONTRACT CARPETS LTD • Tel 00353 1450 1514 • Fax 00353 1450 1515

Carpet Tiles

A-Line 70+	Bitumen	JM400	JM300	-
A-Line 8001	Bitumen	JM400	JM300	-
A-Line 9001	Bitumen	JM400	JM300	-
A-Line 10001	Bitumen	JM400	JM300	-
A-Line 10002	Bitumen	JM400	JM300	-
A-Line 11001	Bitumen	JM400	JM300	-
A-Line 11002	Bitumen	JM400	JM300	-
A-Line 12001	P V C	-	JM300	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
A-Line 12002	P V C	-	JM300	-
A-Line 13001	Bitumen	JM400	JM300	-
A-Line 13002	Bitumen	JM400	JM300	-
A-Line 14001	Bitumen	JM400	JM300	-
A-Line 14002	Bitumen	JM400	JM300	-
A-Line 14003	Bitumen	JM400	JM300	-
A-Line 14004	Bitumen	JM400	JM300	-
A-Line 14005	Bitumen	JM400	JM300	-
A-Line 15001	Bitumen	JM400	JM300	-
A-Line 16001	P V C	-	JM300	-
A-Line 17001	Bitumen	JM400	JM300	-
A-Line Invision Cosmopolitan	Nexus®	-	JM300	-
A-Line Invision Tussah	Nexus®	-	JM300	-
A-Line Invision Vibe	Nexus®	-	JM300	-
A-Line J & J Radius	Nexus®	-	JM300	-
A-Line j & J Realm	Nexus®	-	JM300	-
A-Line J & J Shaken	Nexus®	-	JM300	-
A-Line J & J Stirred	Nexus®	-	JM300	-
AML reflect	Bitumen	JM400	JM300	-
Healthcare				
Hospi - Range	HD Gel	JM400, JM200, JM700 -		JM800
Spike Proof				
Albatros II	Woven Synthetic	JM400, JM200	JM200	JM800
Ballantrae Classic	Woven Synthetic	JM400, JM200	JM200	JM800
Tretford				
Cord Carpet	Jute Hessian	JM400	-	JM800
Tile	P V C	-	JM300	-
ANGLO FELT INDUSTRIES LTD. • Tel 01706 853513 • Fax 01706 853625				
Level It	Felt Underlay	-	JM200	-
ANKER TEPPICHBODEN • Tel 01502 733511 • Fax 0870 7060129				
Range	Action Bac	JM400, JM200	JM200	JM800
Range	Woven	JM400	-	JM800
Range	P V C	JM500, JM700	-	-
Tiles - Range	Bitumen	JM400	JM300	-
WILLIAM ARMES LTD • Tel 01787 372988 • Fax 01787 379383				
Dandy Sisal	Rubber Latex	JM900	-	JM800
Dandycoco Herring Bone	Rubber Latex	JM900	-	JM800
Dandycoco Panama	Rubber Latex	JM900	-	JM800
Evergreen	Fibre Bonded	JM900	-	JM800
Fitzwell Entrance Matting	P V C	JM900	-	-
Gibraltar	Rubber Latex	JM900	-	-
ARMSTRONG FLOOR PRODUCTS UK LTD • Tel 01235 554848 • Fax 01235 553583				
Resilient Range				
Cenit	P V C	JM500, JM700	-	*
Contour	P V C	JM500, JM700	-	*
Contract Interior	P V C	JM500, JM700	-	*
Contract Interior Acoustic	P V C	JM500, JM700	-	*
Favourite	P V C	JM500, JM700	-	*
Imperial	P V C	JM500, JM700	-	*
Medintech	P V C	JM500, JM700	-	*
Merit	P V C	JM500, JM700	-	*
Perspectives	P V C	JM500, JM700	-	*
Protech	P V C	JM500, JM700	-	*
Royal	P V C	JM500, JM700	-	*
Safeguard	P V C	JM500, JM700	-	*
Safeguard Design	P V C	JM500, JM700	-	*
Scala	P V C	JM500, JM700	-	*
Solid	P V C	JM500, JM700	-	*

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Timberline	P V C	JM500, JM700	-	*
Timberline Acoustic	P V C	JM500, JM700	-	*
Translations	P V C	JM500, JM700	-	*
Transparency	P V C	JM500, JM700	-	*
Wall Flex / Design	P V C	JM500, JM700	-	*
Waterelite	P V C	JM500, JM700	-	*

* for vertical bonds please refer to our technical department

ASSOCIATED WEAVERS (EUROPE) LTD. • Tel 01422 431100 • Fax 01422 431105

Park Lane	Action Bac	JM400	JM200	JM800
Gladiator	Waterproof Gel Foam	JM400	-	JM800

ATLAS CARPETS • Tel 01908 308777 • Fax 01908 308775

Around Town	Action Bac	JM400, JM200	JM200	JM800
Avenue Montaigne	Action Bac	JM400, JM200	JM200	JM800
Badlands	Action Bac	JM400, JM200	JM200	JM800
Beaux Arts	Action Bac	JM400, JM200	JM200	JM800
Brampton	Action Bac	JM400, JM200	JM200	JM800
Bubbles	Action Bac	JM400, JM200	JM200	JM800
Cabana	Action Bac	JM400, JM200	JM200	JM800
Cable	Action Bac	JM400, JM200	JM200	JM800
Campanile	Action Bac	JM400, JM200	JM200	JM800
Catwalk	Action Bac	JM400, JM200	JM200	JM800
Chartwell	Action Bac	JM400, JM200	JM200	JM800
Cipriani	Action Bac	JM400, JM200	JM200	JM800
Circle Back	Action Bac	JM400, JM200	JM200	JM800
Composite	Action Bac	JM400, JM200	JM200	JM800
Contour	Action Bac	JM400, JM200	JM200	JM800
Cool	Action Bac	JM400, JM200	JM200	JM800
Cortona	Action Bac	JM400, JM200	JM200	JM800
Cozumel	Action Bac	JM400, JM200	JM200	JM800
Dimensions	Action Bac	JM400, JM200	JM200	JM800
Dots	Action Bac	JM400, JM200	JM200	JM800
Eaton	Action Bac	JM400, JM200	JM200	JM800
Element	Action Bac	JM400, JM200	JM200	JM800
Engraving	Action Bac	JM400, JM200	JM200	JM800
Etching	Action Bac	JM400, JM200	JM200	JM800
Expression	Action Bac	JM400, JM200	JM200	JM800
Expressway	Action Bac	JM400, JM200	JM200	JM800
Extracts	Action Bac	JM400, JM200	JM200	JM800
Fab	Action Bac	JM400, JM200	JM200	JM800
Field Rotation	Action Bac	JM400, JM200	JM200	JM800
Freehand	Action Bac	JM400, JM200	JM200	JM800
Fuse Box	Action Bac	JM400, JM200	JM200	JM800
Grande Terrace	Action Bac	JM400, JM200	JM200	JM800
Hip	Action Bac	JM400, JM200	JM200	JM800
Iguazu	Action Bac	JM400, JM200	JM200	JM800
Inca	Action Bac	JM400, JM200	JM200	JM800
Indian mission	Action Bac	JM400, JM200	JM200	JM800
Inizio	Action Bac	JM400, JM200	JM200	JM800
Inside Out	Action Bac	JM400, JM200	JM200	JM800
Jaspe	Action Bac	JM400, JM200	JM200	JM800
Javari	Action Bac	JM400, JM200	JM200	JM800
Jazzed	Action Bac	JM400, JM200	JM200	JM800
Kago	Action Bac	JM400, JM200	JM200	JM800
Live Wire	Action Bac	JM400, JM200	JM200	JM800
Moda	Action Bac	JM400, JM200	JM200	JM800
Mosaico	Action Bac	JM400, JM200	JM200	JM800
Neoclassic	Action Bac	JM400, JM200	JM200	JM800
Norfolk	Action Bac	JM400, JM200	JM200	JM800
Orinoco	Action Bac	JM400, JM200	JM200	JM800
Overture	Action Bac	JM400, JM200	JM200	JM800
Paradiso	Action Bac	JM400, JM200	JM200	JM800
Parterre	Action Bac	JM400, JM200	JM200	JM800
Perspective	Action Bac	JM400, JM200	JM200	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Positano	Action Bac	JM400, JM200	JM200	JM800
Post Modern	Action Bac	JM400, JM200	JM200	JM800
Prarie School	Action Bac	JM400, JM200	JM200	JM800
Raw	Action Bac	JM400, JM200	JM200	JM800
Relief	Action Bac	JM400, JM200	JM200	JM800
Renaissance	Action Bac	JM400, JM200	JM200	JM800
Round & Round	Action Bac	JM400, JM200	JM200	JM800
Rue Marche	Action Bac	JM400, JM200	JM200	JM800
Sashi	Action Bac	JM400, JM200	JM200	JM800
Sgraffito	Action Bac	JM400, JM200	JM200	JM800
Shape	Action Bac	JM400, JM200	JM200	JM800
Spice Route	Action Bac	JM400, JM200	JM200	JM800
Squared Off	Action Bac	JM400, JM200	JM200	JM800
Straight & Narrow	Action Bac	JM400, JM200	JM200	JM800
Strathmore	Action Bac	JM400, JM200	JM200	JM800
Striation	Action Bac	JM400, JM200	JM200	JM800
Structures	Action Bac	JM400, JM200	JM200	JM800
Surface	Action Bac	JM400, JM200	JM200	JM800
Surfaces 3	Action Bac	JM400, JM200	JM200	JM800
Swirls	Action Bac	JM400, JM200	JM200	JM800
Tamarisk	Action Bac	JM400, JM200	JM200	JM800
Tosca	Action Bac	JM400, JM200	JM200	JM800
Tram	Action Bac	JM400, JM200	JM200	JM800
Upton	Action Bac	JM400, JM200	JM200	JM800

AXMINSTER CARPETS LTD • Tel 01297 32244 • Fax 01297 35241

Antique Splendour	Jute	JM400	JM200	JM800
Devonia Collection	Jute	JM400	JM200	JM800
Exeter	Jute	JM400	JM200	JM800
Exmoor	Jute	JM400	JM200	JM800
Glandore	Jute	JM400	JM200	JM800
Grosvenor Square	Jute	JM400	JM200	JM800
Inismore	Jute	JM400	JM200	JM800
Jacob Twist & Tweed	Jute	JM400	JM200	JM800
Moorland Collection	Jute	JM400	JM200	JM800
Natural Plaid	Jute	JM400	JM200	JM800
Oxford Tweed	Jute	JM400	JM200	JM800
Princetown	Jute	JM400	JM200	JM800
Royal Axminster	Jute	JM400	JM200	JM800
Royal Clovelly	Jute	JM400	JM200	JM800
Royal Dartmouth	Jute	JM400	JM200	JM800
Royal Seaton	Jute	JM400	JM200	JM800
Salcombe	Jute	JM400	JM200	JM800
Shaldon	Jute	JM400	JM200	JM800
Simply Natural	Jute	JM400	JM200	JM800
Tamar	Jute	JM400	JM200	JM800
Torbay	Jute	JM400	JM200	JM800

BALL AND YOUNG (BRITISH VITA) LTD • Tel 01536 200502 • Fax 01536 269554

Cloud 9 Contract	PE film	-	JM200	-
Cloud 9 Flame Retardant (4, 6, 8)	PE film	-	JM200	-
Cloud 9 Radiance	PE film	-	JM200	-
Cloud 9 Silver Lining	PE film	-	JM200	-
Cloud 9 Super Contract	PE film	-	JM200	-
Fronrunner	PE film	-	JM200	-

BALTA INDUSTRIES • Tel 0032 566 22211 • Fax 0032 566 22355

Afro	Action Bac	JM400, JM200	JM200	JM800
Ambiente	Action Bac	JM400, JM200	JM200	JM800
Andaluz	Felt	JM400, JM200	JM200	JM800
Berga	Action Bac	JM400, JM200	JM200	JM800
Bali Twist	Felt	JM400, JM200	JM200	JM800
Blackjack	Felt	JM400, JM200	JM200	JM800
Casadesign	Action Bac	JM400, JM200	JM200	JM800
Casadesign	Felt	JM400, JM200	JM200	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Casarella	Action Bac	JM400, JM200	JM200	JM800
Corsa	Action Bac	JM400, JM200	JM200	JM800
Curly	Felt	JM400, JM200	JM200	JM800
Desert Twist	Action Bac	JM400, JM200	JM200	JM800
Diamond - Tech	Action Bac	JM400	JM200	JM800
Diva	Felt	JM400, JM200	JM200	JM800
Domino	Felt	JM400, JM200	JM200	JM800
Dura - Tech Matting	P V C	JM900	-	-
Fairfield Twist	Action Bac	JM400, JM200	JM200	JM800
Elysee	Action Bac	JM400, JM200	JM200	JM800
Entrada	P V C	JM900	-	-
Floors That Teach	Action Bac	JM400	JM200	JM800
Four Aces	Felt	JM400, JM200	JM200	JM800
Full House	Felt	JM400, JM200	JM200	JM800
Fusion/ Fusion Shaggy	Felt	JM400, JM200	JM200	JM800
Fiesta	Action Bac	JM400, JM200	JM200	JM800
Gala	Action Bac	JM400, JM200	JM200	JM800
Gala	Felt	JM400, JM200	JM200	JM800
Gamma - Tech Impervious	Comp. Gel Foam	JM400	-	JM800
Gianni	Action Bac	JM400, JM200	JM200	JM800
Genova	Action Bac	JM400, JM200	JM200	JM800
Gold - Tech	Action Bac	JM400	JM200	JM800
Health - Tech Impervious	Comp. Gel Foam	JM400	-	JM800
Impulse	Action Bac	JM400	JM200	JM800
Intromat	P V C	JM900	-	-
Kasghar	Action Bac	JM400, JM200	JM200	JM800
Kingston	Felt	JM400, JM200	JM200	JM800
Lucky 7	Felt	JM400, JM200	JM200	JM800
Med - Tech Impervious	Comp. Gel Foam	JM400	-	JM800
Mega - Tech	Action Bac	JM400	JM200	JM800
Moon Shadow	Felt	JM400, JM200	JM200	JM800
Multi - Tech Impervious	Comp. Gel Foam	JM400	-	JM800
Natura	Woven	JM400	-	JM800
Natural Square	Action Bac	JM400, JM200	JM200	JM800
Natural Weave	Action Bac	JM400, JM200	JM200	JM800
Neon Black Light	Action Bac	JM400	JM200	JM800
Noble Saxony	Action Bac / Felt	JM400, JM200	JM200	JM800
Nova - Tech	Action Bac	JM400	JM200	JM800
Palm Springs	Action Bac	JM400, JM200	JM200	JM800
Prestige Berber Twist	Action Bac	JM400, JM200	JM200	JM800
Prestige Twist	Felt	JM400, JM200	JM200	JM800
Prima	Action Bac	JM400, JM200	JM200	JM800
Primavera	Felt	JM400, JM200	JM200	JM800
Rasta	Felt	JM400, JM200	JM200	JM800
Rustic Shaggy	Felt	JM400, JM200	JM200	JM800
Rustic Twist	Felt	JM400, JM200	JM200	JM800
Sahara	Action Bac	JM400 JM200	JM200	JM800
Scala	Felt	JM400, JM200	JM200	JM800
San Diego	Action Bac	JM400, JM200	JM200	JM800
Shaggy Finesse	Action Bac	JM400, JM200	JM200	JM800
Shepard Twist	Action Bac	JM400, JM200	JM200	JM800
Stainsafe Collection	Action Bac	JM400, JM200	JM200	JM800
Star - Tech	Action Bac	JM400	JM200	JM800
Techno	Action Bac	JM400, JM200	JM200	JM800
Tempo	Felt	JM400, JM200	JM200	JM800
Twist - Tech	Action Bac	JM400	JM200	JM800
Twisty	Felt	JM400, JM200	JM200	JM800
Velvet Twist	Action Bac	JM400 JM200	JM200	JM800
Versailles	Action Bac	JM400 JM200	JM200	JM800
Wellington	Woven	JM400	-	JM800
Wiltax	Woven	JM400	-	JM800
Wonderweave	Felt	JM400, JM200	JM200	JM800
Wooldesign	Action Bac	JM400, JM200	JM200	JM800
Zeta - Tech Impervious	Comp. Gel Foam	JM400	-	JM800

Tiles

Alpha - Tech	Bitumen / Non-Woven	JM400	JM300	-
Archi - Tech	Bitumen / Non-Woven	JM400	JM300	-
Beta - Tech	Bitumen / Non-Woven	JM400	JM300	-
Beta - Tech	P V C	JM900	-	-
Delta - Tech	Bitumen / Non-Woven	JM400	JM300	-
Hi - Tech	Bitumen / Non-Woven	JM400	JM300	-
Inter - Tech	Bitumen / Non-Woven	JM400	JM300	-
Mega - Tech	Bitumen / Non-Woven	JM400	JM300	-
Sigma - Tech	Bitumen / Non-Woven	JM400	JM300	-

BOND WORTH LTD • Tel 01562 745000 • Fax 01562 732827

Olympus 4	Jute / Latex	JM400, JM200	JM200	JM800
Axminster	Jute	JM400	-	JM800
Bondax Tile	Mexphalte	JM400	JM300	-

BRINTONS LTD • Tel 01562 635446 • Fax 01562 634704

Abbeyglen	Jute / Synthetic	JM400	-	JM800
Abotsford Collection	Jute / Synthetic	JM400	-	JM800
Bell Twist	Jute / Synthetic	JM400	-	JM800
Bell Twist Tile	Bitumen	JM400	JM300	-
Classic Florals Petite Fleur	Jute / Synthetic	JM400	-	JM800
Classic Florals Tapestry	Jute / Synthetic	JM400	-	JM800
Classic Florals Toile	Jute / Synthetic	JM400	-	JM800
Designer	Jute / Synthetic	JM400	-	JM800
Duet	Synthetic	JM400	-	JM800
Escape	Jute / Synthetic	JM400	-	JM800
Finepoint	Jute / Synthetic	JM400	-	JM800
Fresco	Jute / Synthetic	JM400	-	JM800
Galleria	Jute / Synthetic	JM400	-	JM800
Kinetic	Jute / Synthetic	JM400	-	JM800
Laura Ashley Collection	Jute / Synthetic	JM400	-	JM800
Life Central Bamboo	Synthetic	JM400	-	JM800
Life Central Chess	Synthetic	JM400	-	JM800
Life Central Flatweave Stitch	Synthetic	JM400	-	JM800
Life Central Moss	Synthetic	JM400	-	JM800
Life Central Pearl	Synthetic	JM400	-	JM800
Life Central Rope	Jute	JM400	-	JM800
Life Core Calico	Synthetic	JM400	-	JM800
Life Core Quattro	Jute	JM400	-	JM800
Life Core Rattan	Jute	JM400	-	JM800
Life Core Twill	Synthetic	JM400	-	JM800
Life Core Wicker Trellis	Jute	JM400	-	JM800
Life Woven Axminster	Jute / Synthetic	JM400	-	JM800
Life Woven Wilton	Jute / Synthetic	JM400	-	JM800
Llewellyn Bowan Collection	Jute / Synthetic	JM400	-	JM800
Majestic	Jute / Synthetic	JM400	-	JM800
Marquis	Jute / Synthetic	JM400	-	JM800
Marrakesh	Jute / Synthetic	JM400	-	JM800
Paloma	Jute / Synthetic	JM400	-	JM800
Pure Living	Jute / Synthetic	JM400	-	JM800
Regina International	Jute / Synthetic	JM400	-	JM800
Renaissance	Jute / Synthetic	JM400	-	JM800
Stripes Collection	Jute / Synthetic	JM400	-	JM800

BROCKWAY CARPETS LTD • Tel 01562 747877 • Fax 01562 752010

Amore	Polydrefit	JM400, JM200	JM200	JM800
Aspen 50	Polydrefit	JM400, JM200	JM200	JM800
Berber Classic	Polydrefit	JM400, JM200	JM200	JM800
Cavendish	Polydrefit	JM400, JM200	JM200	JM800
Craftsman Elite	Polydrefit	JM400, JM200	JM200	JM800
Cresta	Polydrefit	JM400, JM200	JM200	JM800
Cresta Heathers	Polydrefit	JM400, JM200	JM200	JM800
Cresta Supreme	Polydrefit	JM400, JM200	JM200	JM800
Cresta Supreme Heathers	Polydrefit	JM400, JM200	JM200	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Fairfield Twist	Polydref	JM400, JM200	JM200	JM800
Florian	Polydref	JM400, JM200	JM200	JM800
Lakeland Herdwick	Polydref	JM400, JM200	JM200	JM800
Orion	Polydref	JM400, JM200	JM200	JM800
Orion Twist Major	Polydref	JM400, JM200	JM200	JM800
Twinfold	Polydref	JM400, JM200	JM200	JM800
Vogue	Polydref	JM400, JM200	JM200	JM800

BURMATEX LTD • Tel 01924 262525 • Fax 01924 280033

Mode - Decorative Tiles

Range	P V C	JM700	-	-
-------	-------	-------	---	---

Tiles

Academy	Anchorite B / Polyester	JM400, JM700	JM300	-
Artemis	Anchorite B / Polyester	JM400, JM700	JM300	-
Axis	Bitumen/Felt	JM400, JM700	JM300	-
Barrier	Anchorite B / Polyester	JM400, JM700	JM300	-
Chevroly 50	Anchorite B / Polyester	JM400, JM700	JM300	-
Code	Anchorite B / Polyester	JM400, JM700	JM300	-
Cordiale	Anchorite B / Polyester	JM400, JM700	JM300	-
Grandee	Anchorite B / Polyester	JM400, JM700	JM300	-
Grimebuster 50	Anchorite B / Polyester	JM400, JM700	JM300	-
Groove	Anchorite B / Polyester	JM400, JM700	JM300	-
Independent	Anchorite B / Polyester	JM400, JM700	JM300	-
Infinity 24	Anchorite B / Polyester	JM400, JM700	JM300	-
Lateral	Anchorite B / Polyester	JM400, JM700	JM300	-
Loom	Anchorite B / Polyester	JM400, JM700	JM300	-
Origin	Bitumen/Felt	JM400, JM700	JM300	-
Rialto	Anchorite B / Polyester	JM400, JM700	JM300	-
Sector	Bitumen/Felt	JM400, JM700	JM300	-
Spin	Bitumen/Felt	JM400, JM700	JM300	-
Tivoli 24	Bitumen/Felt	JM400, JM700	JM300	-
Tivoli Online	Bitumen/Felt	JM400, JM700	JM300	-
Velour Excel	Anchorite B / Polyester	JM400, JM700	JM300	-
Vibe	Bitumen/Felt	JM400, JM700	JM300	-
Zip	Anchorite B / Polyester	JM400, JM700	JM300	-

Carpet Rolls

3230 Classic	Fibrebonded	JM400	-	JM800
4200 Sidewalk	Fibrebonded	JM400	-	JM800
4400 Broadway	Fibrebonded	JM400	-	JM800
5500 Luxury	Fibrebonded	JM400	-	JM800
7700 Grimebuster	Fibrebonded	JM900	-	JM800
7800 Chevroly	Fibrebonded	JM900	-	JM800
Barrier Matting	P V C	JM900	-	-
Lateral	Fibrebonded	JM400	-	JM800

CARPET LINE DIRECT • Tel 01642 250500 • Fax 01642 252929

Adenture	Action Bac	JM400, JM200	JM200	JM800
Alicante Felt	Felt	JM400, JM200	JM200	JM800
Ancona	Felt	JM400, JM200	JM200	JM800
Aztec	Action Bac	JM400, JM200	JM200	JM800
Bedford / Primavera	Latex Foam	JM400, JM200	-	JM800
Besoke 30,40,50 & 60oz	Secondary	JM400, JM200	JM200	JM800
Border Twist	Felt	JM400, JM200	JM200	JM800
California Twist	Action Bac	JM400, JM200	JM200	JM800
Can Can	Gel Foam	JM400	-	JM800
Chambray	Action Bac	JM400, JM200	JM200	JM800
Crofter	Felt	JM400, JM200	JM200	JM800
Desert Shades	Action Bac	JM400, JM200	JM200	JM800
Detroit	Gel Foam	JM400	-	JM800
Discovery	Action Bac	JM400, JM200	JM200	JM800
Diva	Felt	JM400, JM200	JM200	JM800
Entra Matting 2m Gel	Gel Foam	JM400	-	JM800
Fairfield Supreme	Secondary	JM400, JM200	JM200	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Fulford	Secondary	JM400, JM200	JM200	JM800
Grace Felt	Felt	JM400, JM200	JM200	JM800
Gracelands	Felt	JM400, JM200	JM200	JM800
Harrow Twist	Felt	JM400, JM200	JM200	JM800
Hercules	Felt	JM400, JM200	JM200	JM800
Heritage Heathers	Secondary	JM400, JM200	JM200	JM800
Indulgence	Secondary	JM400, JM200	JM200	JM800
Jazz	Gel Foam	JM400	-	JM800
Liberty Twist	Felt	JM400, JM200	JM200	JM800
Lifestyle 40 & 50	Secondary	JM400, JM200	JM200	JM800
Luxury	Secondary	JM400, JM200	JM200	JM800
Medoc	Felt	JM400, JM200	JM200	JM800
Napoli	Felt	JM400, JM200	JM200	JM800
Nice	Felt	JM400, JM200	JM200	JM800
Noble Saxony	Secondary	JM400, JM200	JM200	JM800
Noble Saxony Felt	Felt	JM400, JM200	JM200	JM800
Nocturne	Secondary	JM400, JM200	JM200	JM800
Opulence	Secondary	JM400, JM200	JM200	JM800
Osaka	Felt	JM400, JM200	JM200	JM800
Prestige Berber 2010	Secondary	JM400, JM200	JM200	JM800
Prestige Deluxe	Secondary	JM400, JM200	JM200	JM800
Primavera Tile	Gel Foam	JM400	-	-
Revolution	Secondary	JM400, JM200	JM200	JM800
Revolution Heathers	Secondary	JM400, JM200	JM200	JM800
Rhino	Gel Foam	JM400	-	JM800
Rustic Heathers 40 & 50	Secondary	JM400, JM200	JM200	JM800
Salsa	Felt	JM400, JM200	JM200	JM800
San Antonio	Secondary	JM400, JM200	JM200	JM800
SS Favourite Elite & Premium	Secondary	JM400, JM200	JM200	JM800
Stainclear Heathers	Secondary	JM400, JM200	JM200	JM800
Stainsafe Imperial	Secondary	JM400, JM200	JM200	JM800
Startwist Supreme	Secondary	JM400, JM200	JM200	JM800
Toledo	Felt	JM400, JM200	JM200	JM800
Trafalgar	Felt	JM400, JM200	JM200	JM800
Triple Twist Deluxe, Luxury & Supreme	Secondary	JM400, JM200	JM200	JM800
Tweed	Secondary	JM400, JM200	JM200	JM800
Wembley	Secondary	JM400, JM200	JM200	JM800
Wicker	Felt	JM400, JM200	JM200	JM800

THE CARPET TILE BROKERS LTD. • Tel 01629 57292 • Fax 01629 57282

Baffin	Bitumen	JM400	JM300	-
Baltic	Bitumen	JM400	JM300	-
Barracuda	Bitumen	JM400	JM300	-
Beluga	Bitumen	JM400	JM300	-
Blues	Bitumen	JM400	JM300	-
Dolphin	Bitumen	JM400	JM300	-
Grand Banks	Bitumen	JM400	JM300	-
Mako	Bitumen	JM400	JM300	-
Manta	Bitumen	JM400	JM300	-
Marlin	Bitumen	JM400	JM300	-
Nares	Bitumen	JM400	JM300	-
Nawhal	Bitumen	JM400	JM300	-
Neptune	Bitumen	JM400	JM300	-
Orca	Bitumen	JM400	JM300	-
Reef	Bitumen	JM400	JM300	-
Silurian	Bitumen	JM400	JM300	-
Tarpen	Bitumen	JM400	JM300	-
Tuborg	Bitumen	JM400	JM300	-

CAVALIER CARPETS LTD • Tel 01254 268000 • Fax 01254 268001

Axminster

Arlington	Jute / Synthetic	JM400	-	JM800
Inspirations	Jute / Synthetic	JM400	-	JM800
Monmatre	Jute / Synthetic	JM400	-	JM800
Pennant	Jute / Synthetic	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Savannah	Jute / Synthetic	JM400	-	JM800
Wilton				
Chelsea Stripe	Jute / Synthetic	JM400	-	JM800
Decade	Jute / Synthetic	JM400	-	JM800
Decade Textures	Jute / Synthetic	JM400	-	JM800
Double Decade	Jute / Synthetic	JM400	-	JM800
Triple Decade	Jute / Synthetic	JM400	-	JM800
Tufted				
Adobe	HD Impervious Foam	JM400, JM200	-	JM800
Architect	Lobac / Hessian	JM400	-	JM800
Avantgard Collection	Jute Hessian	JM400	-	JM800
Avantgard Collection	HD Impervious Foam	JM400, JM200	-	JM800
Cartouche	Jute Hessian	JM400	-	JM800
Confetti	Jute Hessian	JM400	-	JM800
Country Collection	Jute Hessian	JM400	-	JM800
Criterion	Jute Hessian	JM400	-	JM800
Darwen	Synthetic	JM400	-	JM800
Fineweave	Jute Hessian	JM400	-	JM800
Guildhall twist	Jute Hessian	JM400	-	JM800
Liberty Twist	Jute Hessian	JM400	-	JM800
Osiris	Jute Hessian	JM400	-	JM800
Rustic Choice	Lobac / Hessian	JM400	-	JM800
Rustic Life	Lobac / Hessian	JM400	-	JM800
Rustic Tweed	Lobac / Hessian	JM400	-	JM800
Saracen	HD Impervious Foam	JM400, JM200	-	JM800
Shepherds Colection	Jute Hessian	JM400	-	JM800
Stainless Collection	Lobac / Hessian	JM400	-	JM800
Tumbletex	Jute Hessian	JM400	-	JM800
Urban Choice	Jute Hessian	JM400	-	JM800
Woolsack	Jute / Synthetic	JM400	-	JM800
Tiles				
Chroma	P V C	-	JM300	-
Confetti	Bitumen / Felt	-	JM300	-
Corvette	Bitumen / Felt	-	JM300	-
Darwen	Bitumen / Felt	-	JM300	-
Pagent	Bitumen / Felt	-	JM300	-
Saraband	P V C	-	JM300	-
Solus	Bitumen / Felt	-	JM300	-
Sphinx	Bitumen / Felt	-	JM300	-
CCM CALDEW CARPET MANUFACTURERS • Tel 01228 810568 • Fax 01228 810582				
Custom 34	Jute Hessian	JM400, JM200	JM200	JM800
Custom 38	Jute Hessian	JM400, JM200	JM200	JM800
Custom 42	Jute Hessian	JM400, JM200	JM200	JM800
Custom 45	Jute Hessian	JM400, JM200	JM200	JM800
Customax 9 Row	Jute / Latex	JM400, JM200	JM200	JM800
Stockax 9 Row	Jute / Latex	JM400, JM200	JM200	JM800
CFS CARPETS (CONTRACT FLOORING SALES) • Tel 0870 6074321 • Fax 0870 4280787				
Tiles				
Aquarius	Mexphalte	JM400	JM300	-
Chinook	Mexphalte	JM400	JM300	-
Classic Loop	Mexphalte	JM400	JM300	-
Classic Rib	Mexphalte	JM400	JM300	-
Classic Velour	Mexphalte	JM400	JM300	-
Definition	Mexphalte	JM400	JM300	-
Endeavour	Mexphalte	JM400	JM300	-
Formation	Mexphalte	JM400	JM300	-
Frontier Design	Mexphalte	JM400	JM300	-
Frontier Plus	Mexphalte	JM400	JM300	-
Generation	Mexphalte	JM400	JM300	-
Graduation	Mexphalte	JM400	JM300	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

Lobby	Mexphalte	JM400	JM300	-
New Mythology	Mexphalte	JM400	JM300	-
New Prairie	Mexphalte	JM400	JM300	-
New Tornado	Mexphalte	JM400	JM300	-
New Typhoon	Mexphalte	JM400	JM300	-
New Vocation	Mexphalte	JM400	JM300	-
Opus	Mexphalte	JM400	JM300	-
Pioneer	Mexphalte	JM400	JM300	-
Precision	Mexphalte	JM400	JM300	-
Republic	Mexphalte	JM400	JM300	-
Wavelength	Mexphalte	JM400	JM300	-

Carpets

Acropolis	Actionbac	JM400	-	JM800
Alumina	Actionbac	JM400	-	JM800
Barricade	Rubber Waffle	JM400	-	JM800
Beachcraft	P V C	JM500	-	-
Berkshire	P V C	JM500	-	-
Blockade	Hessian	JM400	-	JM800
Caesar	Impervious Gel Foam	JM400	-	JM800
Chinook Sheet	Fibrebonded	JM400	-	JM800
Composition	Actionbac	JM400	-	JM800
Congress	Impervious Gel Foam	JM400, JM200	-	JM800
Compilation	Textile	JM400	-	JM800
Convention Care	Impervious Gel Foam	JM400	-	JM800
Creation	Actionbac	JM400	-	JM800
Duet Nova	Impervious Gel Foam	JM400	-	JM800
Evesham	Impervious Gel Foam	JM400, JM200	-	JM800
Federation	Textile	JM400	-	JM800
Geltron 2000	Impervious Gel Foam	JM400, JM200	-	JM800
Hanbury Care	Impervious Foam	JM400	-	JM800
Harvington	Impervious Gel Foam	JM400, JM200	-	JM800
Hercules	Impervious Gel Foam	JM400	-	JM800
Intuition	Actionbac	JM400	-	JM800
Isis II	Impervious Gel Foam	JM400, JM200	-	JM800
Minstrel	Actionbac	JM400	-	JM800
New Dalmation	Gel Foam	JM400, JM200	-	JM800
New Drever	Rubber Waffle	JM400	-	JM800
New Hurricane Sheet	Fibrebonded	JM400	-	JM800
New Tornado Sheet	Fibrebonded	JM400	-	JM800
New Typhoon Sheet	Fibrebonded	JM400	-	JM800
Norbury Care	Impervious Gel Foam	JM400	-	JM800
Priory	Impervious Gel Foam	JM400, JM200	-	JM800
Precision	Textile	JM400	-	JM800
Recital	Impervious Foam	JM400	-	JM800
Scala/Scala Tonals	Impervious Foam	JM400	-	JM800
Stockdale	Rubber Waffle	JM400	-	JM800
Varsity	Actionbac	JM400	-	JM800

CHECKMATE INDUSTRIES LTD • Tel 01787 477272 • Fax 01787 476334

Tiles

Bridge	Bitumen	JM400	JM300	-
Canasta	Bitumen	JM400	JM300	-
Checkloop NY	Bitumen	JM400	JM300	-
Checkrib Plus	Bitumen	JM400	JM300	-
Checkstar	Bitumen	JM400	JM300	-
Checkstar Plus	Bitumen	JM400	JM300	-
Checkstat Extra	Bitumen	JM400	JM300	-
Checkstat Two	Bitumen	JM400	JM300	-
Developer	Bitumen	JM400	JM300	-
Flotex Tile	P V C	JM500	JM300	-
Heathland	Bitumen	JM400	JM300	-
Iboflor	Bitumen	JM400	JM300	-
Masterflor	Bitumen	JM400	JM300	-
Masterpiece	Bitumen	JM400	JM300	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Masterpiece Two	Bitumen	JM400	JM300	-
Masterpiece XL	Bitumen	JM400	JM300	-
Regulator Cut	Bitumen	JM400	JM300	-
Regulator Loop	Bitumen	JM400	JM300	-
Regulator Pattern	Bitumen	JM400	JM300	-
T 80/20 Tile	Bitumen	JM400	JM300	-

Sheet Material

Accommodation 2	Impervious Foam	JM400	-	JM800
Checkrib Plus	Gel Foam	JM400	-	JM800
Chess	Action Bac	JM400	-	JM800
Countdown	Action Bac	JM400	-	JM800
Liberator	Compressed Gel Foam	JM400	-	JM800
Monopoly Two	Action Bac	JM400	-	JM800
Pontoon	Compressed Gel Foam	JM400	-	JM800
Shelter	Compressed Gel Foam	JM400, JM200	-	JM800
Stylemaster	Compressed Gel Foam	JM400, JM200	-	JM800
Twinloop Two	Compressed Gel Foam	JM400, JM200	-	JM800
Flotex Sheet	P V C	JM500	-	-

CHILTERN CARPET TILES LTD • Tel 01604 648585 • Fax 01604 647482

Ambiance	Bitumen	JM400	JM300	-
Arun	Bitumen	JM400	JM300	-
Choices	Bitumen	JM400	JM300	-
Cocktail	Bitumen	JM400	JM300	-
Concierge	Bitumen	JM400	JM300	-
Elements	Bitumen	JM400	JM300	-
Legacy	Bitumen	JM400	JM300	-
Linea	Bitumen	JM400	JM300	-
Medley	Bitumen	JM400	JM300	-
Mercantile	Bitumen	JM400	JM300	-
Metric Cut	Bitumen	JM400	JM300	-
Metric Loop	Bitumen	JM400	JM300	-
Metric Pattern	Bitumen	JM400	JM300	-
Mosaic	Bitumen	JM400	JM300	-
Nova	Bitumen	JM400	JM300	-
Options	Bitumen	JM400	JM300	-
Peninsula	Bitumen	JM400	JM300	-
Privilege	Bitumen	JM400	JM300	-
Resource	Bitumen	JM400	JM300	-
Seasons	Bitumen	JM400	JM300	-
Shannon	Bitumen	JM400	JM300	-
Shannon Aspects	Bitumen	JM400	JM300	-
Solutions	Bitumen	JM400	JM300	-
Status II	Bitumen	JM400	JM300	-
Status Plain	Bitumen	JM400	JM300	-

CHRISTY CARPETS • Tel 01908 308777 • Fax 01908 308775

Tiles

Tiles	Bitumen	JM400	JM300	-
-------	---------	-------	-------	---

Carpets

Sheet Broadloom	Action Bac	JM400, JM200	JM200	JM800
-----------------	------------	--------------	-------	-------

COLOURSOURCE FLOORING SYSTEMS LTD • Tel 01403 790410 • Fax 01403 791548

All Over The Place	Bitumen / Felt	JM400	JM300	-
Catalyst 2	Bitumen / Felt	JM400	JM300	-
Contour	Bitumen / Felt	JM400	JM300	-
Crystalpoint	Bitumen / Felt	JM400	JM300	-
Fortitude	Bitumen / Felt	JM400	JM300	-
Heatherpoint	Bitumen / Felt	JM400	JM300	-
Linear Perspectives	Bitumen / Felt	JM400	JM300	-
Perfect	Bitumen / Felt	JM400	JM300	-
Providence	Bitumen / Felt	JM400	JM300	-
Rhythms	Bitumen / Felt	JM400	JM300	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

Shoreline	Bitumen / Felt	JM400	JM300	-
Strataline	Bitumen / Felt	JM400	JM300	-
Stratagrid	Bitumen / Felt	JM400	JM300	-
Strataweave	Bitumen / Felt	JM400	JM300	-
Tajine	Bitumen / Felt	JM400	JM300	-
Tapestry	Bitumen / Felt	JM400	JM300	-
Terrain Pattern	Bitumen / Felt	JM400	JM300	-
Work Place	Bitumen / Felt	JM400	JM300	-

COURTISAN CARPETS (UK) LTD • Tel 01744 730016 • Fax 01744 451172

Custom Range	Synthetic	JM400, JM200	JM200	-
Custom Range	Jute / Synthetic	JM400, JM200	JM200	-
Royalux Range	Jute / Synthetic	JM400, JM200	JM200	-
Traditional Classics Range	Jute / Synthetic	JM400, JM200	JM200	-
Traditional Florals Range	Jute / Synthetic	JM400, JM200	JM200	-

CRUCIAL TRADING • Tel 01675 433505 • Fax 01675 433521

Coir Boucle	Latex	JM400	-	-
Coir Herringbone	Latex	JM400	-	-
Coir Panama	Latex	JM400	-	-
Jute Range	Latex	JM400	-	-
Paper Papaflat	Latex	JM400	-	-
Paper Woven	Latex	JM400	-	-
Seagrass	Latex	JM400	-	-
Seagrass Fine	Latex	JM400	-	-
Sisal Range	Latex	JM400	-	-
Sisool Big Boucle Classics	Jute	JM400	-	-
Sisool Small Boucle Classics	Jute	JM400	-	-
Sisool Tric	Jute	JM400	-	-
Wool Range	Jute	JM400	-	-
Wool Range	Synthetic	JM400	-	JM800

DAN FLOOR (UK) LTD • Tel 01454 858014 • Fax 01454 858015

Arena	Envi Bac	JM400, JM200	JM200	JM800
Borolo	Secondary	JM400, JM200	JM200	JM800
Classic Contract	HD Gel Bac (FR)	JM400, JM200	-	JM800
Classic XL	HD Gel Bac (FR)	JM400, JM200	-	JM800
Equinox	Envi Bac	JM400, JM200	JM200	JM800
Equinox Commercial	Envi Bac	JM400, JM200	JM200	JM800
Equinox Commercial	Gel Bac	JM400, JM200	-	-
Equinox Trelis	Envi Bac	JM400, JM200	JM200	JM800
Equinox Trelis	Aqua Bac Impervious	JM400, JM200	-	JM800
Equinox Twist	Envi Bac	JM400, JM200	JM200	JM800
Equinox Twist	Aqua Bac Impervious	JM400, JM200	-	JM800
Equinox Tones	Envi Bac	JM400, JM200	JM200	JM800
Eton	HD Gel Bac (FR)	JM400, JM200	-	JM800
Imola	Envi Bac	JM400, JM200	JM200	JM800
Imola Tile	Bitumen	JM400	JM300	-
Infinity	Envi Bac	JM400, JM200	JM200	JM800
New Generation	Aqua Bac Impervious	JM400, JM200	-	JM800
Response Loop	Envi Bac	JM400, JM200	JM200	JM800
Response Loop	Envi Bac	JM400, JM200	JM200	JM800

DESSO LTD • Tel 01235 554848 • Fax 01235 553583

See Armstrong Floor Products UK Ltd.

Desso Carpet Tiles

Bizz	Polyscan	JM400	JM300	-
Capella	Polyscan	JM400	JM300	-
Entry	Bitumen	JM400	JM300	-
Essence	Bitumen	JM400	JM300	-
Fiori N -Loop Pile	Bitumen / Felt	JM400	JM300	-
Flavia	Polyscan	JM400	JM300	-
Freestyle	Polyscan	JM400	JM300	-
Libra - Lines & Grooves	Polyscan	JM400	JM300	-
Libra Planks	Polyscan	JM400	JM300	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Madison	Bitumen / Felt	JM400	JM300	-
Manhattan	Bitumen / Felt	JM400	JM300	-
Menda	Polyscan	JM400	JM300	-
Metal Planks	Polyscan	JM400	JM300	-
Neo	Polyscan	JM400	JM300	-
Neo Cork	Polyscan	JM400	JM300	-
Palatino	Polyscan	JM400	JM300	-
Pallas - XL	Polyscan	JM400	JM300	-
Patches	Polyscan	JM400	JM300	-
Penta	Polyscan	JM400	JM300	-
Protect	Polyscan	JM400	JM300	-
Pure	Polyscan	JM400	JM300	-
Reclaim	Polyscan	JM400	JM300	-
Scape	Polyscan	JM400	JM300	-
Select Classic	Polyscan	JM400	JM300	-
Sienna	Bitumen / Felt	JM400	JM300	-
Sinta	Bitumen / Felt	JM400	JM300	-
Stratos	Bitumen / Felt	JM400	JM300	-
Supira	Polyscan	JM400	JM300	-
Tempra	Bitumen / Felt	JM400	JM300	-
Tipo	Bitumen / Felt	JM400	JM300	-
Trapez	Polyscan	JM400	JM300	-
Tree	Polyscan	JM400	JM300	-

Desso Broadloom

Allegro	Solid Base - Polyprop.	JM400, JM200	JM200	JM800
Champion	Solid Base - Polyprop.	JM400, JM200	JM200	JM800
Elegance	Polypropylene	JM400, JM200	JM200	JM800
Lumino	Polypropylene	JM400, JM200	JM200	JM800
Marathon	Solid Base - Polyprop.	JM400, JM200	JM200	JM800
Mila	Solid Base - Polyprop.	JM400, JM200	JM200	JM800
Primo	Solid Base - Polyprop.	JM400, JM200	JM200	JM800
Quint	Solid Base - Polyprop.	JM400, JM200	JM200	JM800
Select Classic	Polypropylene	JM400, JM200	JM200	JM800
Sisamo	Solid Base - Polyprop.	JM400, JM200	JM200	JM800
Skara	Polypropylene	JM400, JM200	JM200	JM800
Sparx	Polypropylene	JM400, JM200	JM200	JM800
Tempra	Polypropylene	JM400, JM200	JM200	JM800
Torso	Polypropylene	JM400, JM200	JM200	JM800
Trapez	Polypropylene	JM400, JM200	JM200	JM800
Trax	Polypropylene	JM400, JM200	JM200	JM800
Vista	Solid Base - Polyprop.	JM400, JM200	JM200	JM800
Wilton - Ranges	Polypropylene	JM400, JM200	JM200	JM800

DRURY LANE CARPET CO LTD • Tel 01484 550380 • Fax 01484 543911

Academy	Jute	JM400, JM200	JM200	JM800
Aysgarth	Action Bac	JM400, JM200	JM200	JM800
Bradshaw	Impervious Gel	JM400	-	JM800
Cairo	Action Bac	JM400, JM200	JM200	JM800
Clayton	Gel	JM400	-	JM800
Damascus	Action Bac	JM400, JM200	JM200	JM800
Drury Lane	Hessian	JM400, JM200	JM200	JM800
Eldwick	Action Bac	JM400, JM200	JM200	JM800
Gobi	Action Bac	JM400, JM200	JM200	JM800
Heart	Action Bac	JM400, JM200	JM200	JM800
Heathfield Collection	Jute	JM400, JM200	JM200	JM800
Heaton	Action Bac	JM400, JM200	JM200	JM800
Heaton	Impervious Foam	JM400	-	JM800
Kilburn	Jute	JM400, JM200	JM200	JM800
Kyber	Action Bac	JM400, JM200	JM200	JM800
Leyburn	Action Bac	JM400, JM200	JM200	JM800
Luxor	Action Bac	JM400, JM200	JM200	JM800
Madison	Woven	JM400	-	JM800
Natural Collection	Jute	JM400, JM200	JM200	JM800
Richmond Tweed	Jute	JM400, JM200	JM200	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Rothwell	Action Bac	JM400, JM200	JM200	JM800
Shibden	Gel	JM400	-	JM800
Thornton Sheet	Action Bac	JM400, JM200	JM200	JM800
Thornton Tile	Bitumen	JM400	JM300	-
Wilsden	Action Bac	JM400, JM200	JM200	JM800
Wilsden	Impervious Foam	JM400	-	JM800
Woodhall	Jute	JM400, JM200	JM200	JM800

DURALAY LTD • Tel 01706 213131 • Fax 01706 224915

See Interfloor Ltd

DYNE CARPET TILE CO LTD • Tel 0161 8778877 • Fax 0161 8775610

Astron	Bitumen Felt	JM400	JM300	-
Clearway	Bitumen Felt	JM400	JM300	-
Cross Textures	Bitumen Felt	JM400	JM300	-
Diamonds	Bitumen Felt	JM400	JM300	-
Heavy Velour	Bitumen Felt	JM400	JM300	-
Mitrem	Bitumen Felt	JM400	JM300	-
New Area	Bitumen Felt	JM400	JM300	-
New York	Bitumen Felt	JM400	JM300	-
Series 8	Bitumen Felt	JM400	JM300	-
Tectonic	Bitumen Felt	JM400	JM300	-
Velveteen	Bitumen Felt	JM400	JM300	-

EGE CARPETS LTD • Tel 01257 239000 • Fax 01257 239001

Carre Broadloom	Secondary	JM400, JM200	JM200	JM800
Carre Broadloom	Impervious	JM400, JM200	JM200	JM800
Epoc Accent	Secondary	JM400, JM200	JM200	JM800
Epoc Checkers	Impervious	JM400, JM200	JM200	JM800
Epoca Chess	Secondary	JM400, JM200	JM200	JM800
Epoca Classic	HD Latex	JM400, JM200	-	JM800
Epoca Compact	Secondary	JM400, JM200	JM200	JM800
Epoca Pro	Secondary	JM400, JM200	JM200	JM800
Epoca Ribs	Secondary	JM400, JM200	JM200	JM800
Epoca Titanium	Secondary	JM400, JM200	JM200	JM800
Highline 1100 Express / Std	Secondary	JM400, JM200	JM200	JM800
Highline 1100 Express / Std	HD Latex	JM400, JM200	-	JM800
Highline 630 Express / Std	Secondary	JM400, JM200	JM200	JM800
Highline 630 Express / Std	HD Latex	JM400, JM200	-	JM800
Highline 750 Express / Std	Secondary	JM400, JM200	JM200	JM800
Highline 750 Express / Std	HD Latex	JM400, JM200	-	JM800
Highline 910 Express / Std	Secondary	JM400, JM200	JM200	JM800
Highline 910 Express / Std	HD Latex	JM400, JM200	-	JM800
Highline Express 80/20	Secondary	JM400, JM200	JM200	JM800
Highline Loop	Secondary	JM400, JM200	JM200	JM800
Modular Tile	Comfort Back	JM400	JM300	-
Quadro	HD Latex	JM400, JM200	-	JM800
Rainbow	HD Latex	JM400, JM200	-	JM800
Silk Contract	Secondary	JM400, JM200	JM200	JM800
Texturecare	Impervious	JM400, JM200	-	JM800

ENIA TECSOM UK • Tel 01299 252650 • Fax 01299 253657

Tiles

Avenue Design	Vinyl	-	JM300	-
Camera	Vinyl	-	JM300	-
Confidence	Vinyl	-	JM300	-
Decostructure Concept	Vinyl	-	JM300	-
Decovision Concept	Vinyl	-	JM300	-
Elegance Design	Vinyl	-	JM300	-
Galerie Design	Vinyl	-	JM300	-
Linear Fever Compact	Vinyl	-	JM300	-
Pointe 3620	Vinyl	-	JM300	-
Premium Design	Vinyl	-	JM300	-
Supreme Design	Vinyl	-	JM300	-
T2050 Premium	Vinyl	-	JM300	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
T2510 Variance	Vinyl	-	JM300	-
T3580 City Square	Vinyl	-	JM300	-
T3630 Supreme	Vinyl	-	JM300	-
T3680 Excellence	Vinyl	-	JM300	-
T4120 Galerie	Vinyl	-	JM300	-
T4700 Elegance	Vinyl	-	JM300	-
T4900 Avenue	Vinyl	-	JM300	-
T4910 Boulevard	Vinyl	-	JM300	-

Broadloom

Alumina	Action Bac	JM400, JM200	JM300	-
Audance	Action Bac	JM400, JM200	JM300	-
Bella	Action Bac	JM400, JM200	JM300	-
Camera	Action Bac	JM400, JM200	JM300	-
Calypso	Action Bac	JM400, JM200	JM300	-
Chic	Action Bac	JM400, JM200	JM300	-
Finesse	Action Bac	JM400, JM200	JM300	-
Futura XL	Action Bac	JM400, JM200	JM300	-
Gravel Line,Motive,Structure	Action Bac	JM400, JM200	JM300	-
Perfect	Action Bac	JM400, JM200	JM300	-
Montana	Action Bac	JM400, JM200	JM300	-
Solar	Action Bac	JM400, JM200	JM300	-
Winsor	Action Bac	JM400, JM200	JM300	-
Scope	Action Bac	JM400, JM200	JM300	-
Typo	Action Bac	JM400, JM200	JM300	-
Velvet	Action Bac	JM400, JM200	JM300	-
Versailles	Action Bac	JM400, JM200	JM300	-

FLOORING INDUSTRIES LTD • Tel 01923 239851 • Fax 01923 818564

Americana	Bitumen	JM400	JM300	-
Bamboo	Bitumen	JM400	JM300	-
Chalfont Cord	Bitumen	JM400	JM300	-
Dahlia	Bitumen	JM400	JM300	-
Fuchsia	Bitumen	JM400	JM300	-
Maestro 4000	Bitumen	JM400	JM300	-
Montana	Bitumen	JM400	JM300	-
Narcissi	Bitumen	JM400	JM300	-
Resort	Bitumen	JM400	JM300	-
Tosca Rosa	Bitumen	JM400	JM300	-
Tulip	Bitumen	JM400	JM300	-

FORBO FLOORING • Tel 01592 643777 • Fax 01592 643999

Contract Vinyl

Allura LVT	P V C	JM500, JM700	-	*
Colorex Concept	P V C	JM500, JM700	-	*
Effect	P V C	JM500, JM700	-	*
Eternal Impact	P V C	JM500, JM700	-	*
Eternal Mica	P V C	JM500, JM700	-	*
Eternal Stone	P V C	JM500, JM700	-	*
Eternal Wood	P V C	JM500, JM700	-	*
Eternal Wood Decibel	P V C Foam	JM500, JM700	-	*
SafeStep	P V C	JM500, JM700	-	*
SafeStep Grip	P V C	JM500, JM700	-	*
SafeStep R12	P V C	JM500, JM700	-	*
Smaragd	P V C	JM500, JM700	-	*
SureStep	P V C	JM500, JM700	-	*
Sarlon Quartz	P V C Foam	JM500, JM700	-	*
Sarlon Tech	P V C Foam	JM500, JM700	-	*
Sarlon Traffic	P V C Foam	JM500, JM700	-	*

Nairn Cushion Vinyl

Cushionflor Classic	P V C Foam	JM500, JM700	-	-
Cushionflor Futura	P V C Foam	JM500, JM700	-	-
Cushionflor Impressions	P V C Foam	JM500, JM700	-	-
Cushionflor Reflections	P V C Foam	JM500, JM700	-	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

Cushionflor Signature	P V C Foam	JM500, JM700	-	-
Cushionflor Super Luxury	P V C Foam	JM500, JM700	-	-
Cushionflor Superwood	P V C Foam	JM500, JM700	-	-
Cushionflor Supreme	P V C Foam	JM500, JM700	-	-

Novilon

Nova	P V C	JM500, JM700	-	-
Traffic	P V C	JM500, JM700	-	-
Viva	P V C	JM500, JM700	-	-

* for vertical bonds please refer to our technical department

Flotex Range

Chocflex Acoustic Vinyl	P V C / Foam	JM500, JM700	-	-
Chocflex Sport	P V C Foam / Scrim	JM500, JM700	-	-
Flotex Classic	P V C Foam	JM500, JM700	-	-
Flotex HD	P V C Foam	JM500, JM700	-	-
Flotex Sottsass	P V C Foam	JM500, JM700	-	-
Flotex Sport	P V C Foam / Scrim	JM500, JM700	-	-
Flotex Transport/Marine	PMMA	JM500, JM700	-	-
Flotex Tiles - Contract	P V C / Scrim	JM500, JM700	JM300	-

Coral Range

Coral Brush / Activ	P V C	JM900	-	-
Coral Brush / Activ FR	Synthetic Rubber	JM900	-	-
Coral Classic	P V C	JM900	-	-
Coral Classic FR	Synthetic Rubber	JM900	-	-
Coral Duo	P V C	JM900	-	-
Coral Grip	P V C	JM900	-	-
Coral Luxe	P V C	JM900	-	-
Coral Luxe FR	Synthetic Rubber	JM900	-	-
Safestep	P V C	JM500, JM700	-	*
Safestep Grip	P V C	JM500, JM700	-	*
Safestep R12	P V C	JM500, JM700	-	*
Smaragd	P V C	JM500, JM700	-	*
Surestep	P V C	JM500, JM700	-	*

* for vertical bonds please refer to our technical department

GARRARD WATERS LTD • Tel 01604 669000 • Fax 01604 669004

Tiles

Tiles	Bitumen	JM400	JM300	-
-------	---------	-------	-------	---

Sheet

Sheet	Gel	JM400	-	JM800
Sheet	Impervious Gel Foam (comp)	JM400, JM200	-	JM800
Sheet	Embossed Latex Foam	JM400, JM200	-	JM800
Sheet	Gel Rubber Foam	JM400, JM200	-	JM800
Sheet	Action Bac	JM400, JM200	-	JM800

GASKELL MACKAY CARPETS LTD • Tel 01642 757600 • Fax 01642 75762

Amethyst	Woven Synthetic / Jute	JM400	-	JM800
Aurora Supreme	Hessian	JM400, JM200	JM200	JM800
Broadloom Ranges	Woven Synthetic / Jute	JM400	-	JM800
Coniston	Woven Synthetic / Jute	JM400	-	JM800
Custom Tufted	Hessian	JM400, JM200	JM200	JM800
Derwent	Woven Synthetic / Jute	JM400	-	JM800
Diamond	Woven Synthetic / Jute	JM400	-	JM800
Elysee	Woven Synthetic / Jute	JM400	-	JM800
Enhance	Impervious Gel Foam	JM400	-	JM800
Grasmere	Woven Synthetic / Jute	JM400	-	JM800
Holburn	Woven Synthetic / Jute	JM400	-	JM800
Hotel Bedroom Collection	Woven Synthetic / Jute	JM400	-	JM800
Infinity Inn Stock	Woven Synthetic / Jute	JM400	-	JM800
Inn Collection	Jute	JM400, JM200	JM200	JM800
Inn Stock / Style	Jute	JM400, JM200	JM200	JM800
Kensington	Woven Synthetic / Jute	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Lancastria	Woven Synthetic / Jute	JM400	-	JM800
Onyx	Woven Synthetic / Jute	JM400	-	JM800
Opal	Woven Synthetic / Jute	JM400	-	JM800
Organix	Woven Synthetic / Jute	JM400	-	JM800
Paramount	Hessian	JM400, JM200	JM200	JM800
Pearl	Woven Synthetic / Jute	JM400	-	JM800
Sara	Woven Synthetic / Jute	JM400	-	JM800
Tartan	Jute	JM400, JM200	JM200	JM800
Topaz	Woven Synthetic / Jute	JM400	-	JM800
Ullswater	Woven Synthetic / Jute	JM400	-	JM800
Windemere	Woven Synthetic / Jute	JM400	-	JM800

Tiles

Colorado	Bitumen	JM400	JM300	-
Enhanced Rib	Bitumen	JM400	JM300	-
Infinity	Felt	JM400	JM300	-
Montana	Bitumen	JM400	JM300	-

GATES RUBBER CO LTD • Tel 01706 213131 • Fax 01706 224915

See Interfloor Ltd.

GEORGIAN CARPETS • Tel 01827 831430 • Fax 01827 831431

Berber Elite	Jute	JM400, JM200	JM200	JM800
Berber Supreme	Secondary	JM400, JM200	JM200	JM800
Citadel Elite	Jute	JM400, JM200	JM200	JM800
Crystal Stripe	Secondary	JM400, JM200	JM200	JM800
Georgian Barbosa	Jute	JM400, JM200	JM200	JM800
Georgian Berber Style	Jute	JM400, JM200	JM200	JM800
Georgian Cathedral	Jute	JM400, JM200	JM200	JM800
Georgian Deluxe	Jute	JM400, JM200	JM200	JM800
Georgian Greenwich	Secondary	JM400, JM200	JM200	JM800
Georgian Hathaway Twist/Berbers	Jute	JM400, JM200	JM200	JM800
Georgian Lichfield	Jute	JM400, JM200	JM200	JM800
Georgian Luxury Twist	Jute	JM400, JM200	JM200	JM800
Georgian Major Twist	Jute	JM400, JM200	JM200	JM800
Georgian Maxtock	Jute	JM400, JM200	JM200	JM800
Georgian Midnight	Jute	JM400, JM200	JM200	JM800
Georgian Stripes & Plains	Jute	JM400, JM200	JM200	JM800
Georgian Woodstock	Jute	JM400, JM200	JM200	JM800
Greenwich	Jute	JM400, JM200	JM200	JM800
Hathaway Nat 60	Jute	JM400, JM200	JM200	JM800
Impressions	Jute	JM400, JM200	JM200	JM800
Luxor	Jute	JM400, JM200	JM200	JM800
Manor	Jute	JM400, JM200	JM200	JM800
Natural Collocation	Jute	JM400, JM200	JM200	JM800
Natural World	Jute	JM400, JM200	JM200	JM800
New Classic Velvet	Secondary	JM400, JM200	JM200	JM800
New Georgian Velvet	Jute	JM400, JM200	JM200	JM800
New Hathaway Plus	Jute	JM400, JM200	JM200	JM800
Temple Twist	Jute	JM400, JM200	JM200	JM800
Tresco	Jute	JM400, JM200	JM200	JM800
Triumph	Jute	JM400, JM200	JM200	JM800
Various Qualities	Unitary	JM400, JM200	JM200	JM800
Velvet Supreme	Jute	JM400, JM200	JM200	JM800

GERFLOR LTD • Tel 01926 401500 • Fax 01926 401647

Sheet Goods

Actionsport 60	P V C Foam	JM500, JM700	-	*
Aggripa	Acoustic Foam	JM500, JM700	-	*
Aggripa Palette	Acoustic Foam	JM500, JM700	-	*
Ambience	P V C	JM500, JM700	-	*
Architecton	Vinyl to EN 649	JM500, JM700	-	*
Brazilia	P V C	JM500, JM700	-	*
Classic Imperial	Vinyl to EN 649	JM500, JM700	-	*
Elegance Sd	P V C	JM500, JM700	-	*

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Forum EL5	P V C	JM500, JM700	-	*
Griptex	Textile	JM500, JM700	-	*
Indiana Confort	P V C Foam	JM500, JM700	-	*
Indiana Compact	P V C Foam	JM500, JM700	-	*
Insugrip	Textile	JM500, JM700	-	*
Mipolam Activa 250	P V C	JM500, JM700	-	*
Mipolam Elegance 290	P V C	JM500, JM700	-	*
Mipolam Esprit 500	P V C	JM500, JM700	-	*
Mipolam Troplan 100	Vinyl to EN 649	JM500, JM700	-	*
Mural Club	P V C	JM500, JM700	-	*
Mural Ultra	P V C	JM500, JM700	-	*
Nera Classic	P V C	JM500, JM700	-	*
Nera Comfort Wood	P V C Foam	JM500, JM700	-	*
Nera Contract Pixel	P V C	JM500, JM700	-	*
Nera Contract Wood	P V C	JM500, JM700	-	*
Nera Pro	P V C	JM500, JM700	-	*
Nera Tex Plus	Textile	JM500, JM700	-	*
Robust EL7	P V C	JM500, JM700	-	*
SRA Acoustic	Acoustic Foam	JM500, JM700	-	*
Taraflex Performance Plus	P V C Foam	JM500, JM700	-	*
Taraflex Sport M Plus	P V C Foam	JM500, JM700	-	*
Taraflex Surface	P V C Foam	JM500, JM700	-	*
Taralay Comfort Uni	P V C Foam	JM500, JM700	-	*
Taralay Impression Comfort	P V C Foam	JM500, JM700	-	*
Taralay Initial Comfort	P V C	JM500, JM700	-	*
Tarasafe Premium Comfort	P V C Foam	JM500, JM700	-	*
Tarasafe Iona	P V C	JM500, JM700	-	*
Tarasafe Plus	P V C	JM500, JM700	-	*
Tarasafe Standard	P V C	JM500, JM700	-	*
Tarasafe Style	P V C	JM500, JM700	-	*
Tarasafe Super	P V C	JM500, JM700	-	*
Tarasafe Ultra	P V C	JM500, JM700	-	*
Tarasafe Uni	P V C	JM500, JM700	-	*
Tarasafe Ultra Comfort	P V C Foam	JM500, JM700	-	*
Technic EL5	P V C	JM500, JM700	-	*
Texline	Textile	JM500, JM700	-	*
Transiflex Plus	Acoustic Foam	JM500, JM700	-	*
Transit Acoustic Wood	Acoustic Foam	JM500, JM700	-	*
Transit Plus	Acoustic Foam	JM500, JM700	-	*
Universe	Vinyl to EN 649	JM500, JM700	-	*

Tiles

Artline	P V C	JM500, JM700	-	*
Creation	P V C	JM500, JM700	-	*
Saga Looseley Range	P V C	-	JM300	-

* for vertical bonds please refer to our technical department

GRADUS CARPETS • Tel 01625 859000 • Fax 01625 850352

Tiles

Cityscene	Bitumen	JM400	JM300	-
Bodega	Bitumen	JM400	JM300	-
Bodege Cut	Bitumen	JM400	JM300	-
Delta	Bitumen	JM400	JM300	-
Genus	Bitumen	JM400	JM300	-
Latour	Bitumen	JM400	JM300	-
Jaku	Bitumen	JM400	JM300	-
Kata	Bitumen	JM400	JM300	-
Predator	Bitumen	JM400	JM300	-
Roulin	Bitumen	JM400	JM300	-
Sahara	Bitumen	JM400	JM300	-
Square Mile	Bitumen	JM400	JM300	-
Stratus	Bitumen	JM400	JM300	-
Tahoe	Bitumen	JM400	JM300	-
Volnay	Bitumen	JM400	JM300	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

Broadloom

Bodega	Action Bac	JM400, JM200	JM200	JM800
Bodega Cut	Action Bac	JM400, JM200	JM200	JM800
Genus	Action Bac	JM400, JM200	JM200	JM800
Nimbus	Action Bac	JM400, JM200	JM200	JM800
Pacific	Action Bac	JM400, JM200	JM200	JM800
Roulin	Action Bac	JM400, JM200	JM200	JM800
Square Mile	Action Bac	JM400, JM200	JM200	JM800
Stratus	Action Bac	JM400, JM200	JM200	JM800
Syrah Cut	Action Bac	JM400, JM200	JM200	JM800
Syrah Loop	Action Bac	JM400, JM200	JM200	JM800
Volnay	Action Bac	JM400, JM200	JM200	JM800

Impervious

Bodega	P V C / Polyester	JM500, JM700	-	-
Cada Plus	Impervious	JM400	-	JM800
Freeway	Aquabac	JM400	-	JM800
Genus	P V C / Polyester	JM500, JM700	-	-
Minerva	Aquabac	JM400	-	JM800
Pacific	P V C / Polyester	JM500, JM700	-	-
Syrah Cut	P V C / Polyester	JM500, JM700	-	-
Syrah Loop	P V C / Polyester	JM500, JM700	-	-
Volnay	P V C / Polyester	JM500, JM700	-	-

Anker Collection - Broadloom

Aera	Action Bac	JM400, JM200	JM200	JM800
Aera Structure	Action Bac	JM400, JM200	JM200	JM800
Clinique	Action Bac	JM400, JM200	JM200	JM800
Delta	Action Bac	JM400, JM200	JM200	JM800
Roulin	Action Bac	JM400, JM200	JM200	JM800

Anker Collection - Impervious

Aera	P V C	JM500, JM700	-	-
Clinique	P V C	JM500, JM700	-	-
Delta	P V C	JM500, JM700	-	-

Anker Collection - Tiles

Aera	Bitumen	JM400	JM300	-
Delta	Bitumen	JM400	JM300	-

Gradus Matting

Boulevard 5000	P V C / Polyester	JM900	-	-
Boulevard 6000	P V C / Polyester	JM900	-	-

GREENWOOD AND COOPE LTD (CORMAR) • Tel 01204 881234 • Fax 01204 887722

Avebury	Woven Synthetic	JM400, JM200	JM200	JM800
Buchanan	Woven Synthetic	JM400, JM200	JM200	JM800
Highlander	Woven Synthetic	JM400, JM200	JM200	JM800
Home Counties	Woven Synthetic	JM400, JM200	JM200	JM800
Lidesfarne	Woven Synthetic	JM400, JM200	JM200	JM800
Malabar	Woven Synthetic	JM400, JM200	JM200	JM800
Natural Berber Range	Woven Synthetic	JM400, JM200	JM200	JM800
New Hampshire	Woven Synthetic	JM400, JM200	JM200	JM800
New Oaklands	Woven Synthetic	JM400, JM200	JM200	JM800
Primo Range	Woven Synthetic	JM400, JM200	JM200	JM800
Town & Country	Woven Synthetic	JM400, JM200	JM200	JM800

GROSVENOR WILTON COMPANY LTD • Tel 01562 513500 • Fax 01562 822202

Arcadian	Jute / Synthetic / Cotton	JM400	-	JM800
Colorbank	Jute / Synthetic / Cotton	JM400	-	JM800
Extra Luxury	Jute / Synthetic / Cotton	JM400	-	JM800
Extra Super	Jute / Synthetic / Cotton	JM400	-	JM800
Fine Yeoman	Jute / Synthetic / Cotton	JM400	-	JM800
Grosvenor	Jute / Synthetic / Cotton	JM400	-	JM800
Luxury	Jute / Synthetic / Cotton	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

Regatta	Jute / Synthetic / Cotton JM400		-	JM800
Super Brussels	Jute / Synthetic / Cotton JM400		-	JM800
Yeoman/Super Yeoman	Jute / Synthetic / Cotton JM400		-	JM800

HARLEQUIN (British Harlequin plc) • Tel 01892 514888 • Fax 01892 514222

Harlequin Allegro	P V C Foam	JM500, JM700	-	-
Harlequin Cascade	P V C	JM500, JM700	-	-
Harlequin Fiesta	P V C	JM500, JM700	-	-
Harlequin Hi-Shine	P V C	JM500, JM700	-	-
Harlequin Reversible	P V C	JM500, JM700	-	-
Harlequin Showfloor	P V C Foam	JM500, JM700	-	-
Harlequin Standfast	P V C	JM500, JM700	-	-
Harlequin Studio	P V C Foam	JM500, JM700	-	-
Harlequin Tempo	P V C Foam	JM500, JM700	-	-

HECKMONDWIKE FB LTD • Tel 01924 406161 • Fax 01924 413600

Battleship	Fibrebonded	JM900	-	JM800
Broadrib	Fibrebonded	JM400	-	JM800
Conqueror	Fibrebonded	JM400	-	JM800
Diamond	Rubber Crumb	JM900	-	JM800
Dreadnought Sheet	Rubber Waffle	JM900	-	JM800
Dual Care	Impervious Foam	JM400	-	JM800
Gympro	Rubber Crumb	JM900	-	JM800
Hippo	Rubber Waffle	JM900	-	JM800
Hobnail	Fibrebonded	JM400	-	JM800
Iron Duke	Fibrebonded	JM400	-	JM800
Momentum	Fibrebonded	JM400	-	JM800
Montage	Fibrebonded	JM400	-	JM800
Platinum Care	Impervious Foam	JM400	-	JM800
Supacord	Fibrebonded	JM400	-	JM800
Super Drednought	Rubber Crumb	JM900	-	JM800
Total Care	Impervious Foam	JM400	-	JM800
Vanquisher	Rubber Waffle	JM900	-	JM800
Wellington Velour	Fibrebonded	JM400	-	JM800
Zephyr Sheet	Rubber Crumb	JM900	-	JM800

Tiles

Broadrib	Bitumen	JM400	JM300	-
Conqueror	Bitumen	JM400	JM300	-
Diamond	Bitumen	JM400	JM300	-
Dreadnought	Bitumen	JM400	JM300	-
Hobnail	Bitumen	JM400	JM300	-
Momentum	Bitumen	JM400	JM300	-
Montage	Bitumen	JM400	JM300	-
Precipice	Bitumen	JM400	JM300	-
Sticks & Stones	Bitumen	JM400	JM300	-
Supacord	Bitumen	JM400	JM300	-
Super Drednought	Bitumen	JM400	JM300	-
Wellington Velour	Bitumen	JM400	JM300	-
Zephyr	Bitumen	JM400	JM300	-

HERITAGE CARPETS SINGAPORE • Tel 0065 64582334 • Fax 0065 64546012

Broadloom

Imperial Axminster	Woven	JM400	-	JM800
All secondary backed Range	Secondary	JM400, JM200	JM200	JM800
Regal Axminster	Woven	JM400	-	JM800
Starlite Express	Felt	JM400, JM200	JM200	JM800

Tiles

Magnum	T-flex Supra	-	JM300	-
Mandate	Bitumen Felt	-	JM300	-
Manhattan	P V C	-	JM300	-
Mascot	Bitumen Felt	-	JM300	-
Masterfloor	P V C	-	JM300	-
Mayfair	P V C	-	JM300	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Melody 1 and 2	Bitumen Felt	-	JM300	-
Meridien	Bitumen Felt	-	JM300	-
Mezzo	P V C	-	JM300	-
Miko	Bitumen Felt	-	JM300	-
Milano	P V C	-	JM300	-
Milano	P V C	-	JM300	-
Mirage	P V C	-	JM300	-
Modus 1,2,3,and 4	Bitumen Felt	-	JM300	-
Monaco	P V C	-	JM300	-
Mont Blanc	P V C	-	JM300	-
Monte Carlo	P V C	-	JM300	-
Montego	P V C	-	JM300	-
Mystic	Bitumen Felt	-	JM300	-
Tango	P V C	-	JM300	-
Terranova - Oregon	T-flex Supra	-	JM300	-
Torpedo	P V C	-	JM300	-
Toscana	T-flex Supra	-	JM300	-
Tradewind	P V C	-	JM300	-
Trento	T-flex Supra	-	JM300	-

HUGH MACKAY LTD • Tel 01429 892525 • Fax 01429 892530

Durham Cathedral	Woven Jute / Synthetic	JM400	-	JM800
Durham Edition	Jute	JM400	-	JM800
Durham Super Twist 40, 50 and 60	Jute	JM400	-	JM800
Durham Supreme Velvet	Action Bac	JM400	-	JM800
Durham Twist 30	Jute	JM400	-	JM800
Durham Velvet	Action Bac	JM400	-	JM800
Fine Yakcam	Woven Jute / Synthetic	JM400	-	JM800
New Yakcam	Woven Jute / Synthetic	JM400	-	JM800
Yakcam	Woven Jute / Synthetic	JM400	-	JM800

IT C • Tel 0032 51424411 • Fax 0032 51424485

Berber Trail	Action Bac	JM400	-	JM800
Berery Hills	Action Bac	JM400	-	JM800
Birkfield	Action Bac	JM400	-	JM800
Capuccino	Action Bac	JM400	-	JM800
Carma	Felt	JM400, JM200	JM200	JM800
Cleveland	Action Bac	JM400,	-	JM800
Concerto	Action Bac	JM400	-	JM800
Coronet	Action Bac	JM400	-	JM800
Crystal Palace	Action Bac	JM400	-	JM800
Dimensions	Action Bac	JM400	-	JM800
Dorchester	Action Bac	JM400	-	JM800
Fine Twist	Action Bac	JM400	-	JM800
Henley Twist	Action Bac	JM400	-	JM800
Heritage	Action Bac	JM400	-	JM800
Jaguar II	Felt	JM400, JM200	JM200	JM800
Kreta	Felt	JM400, JM200	JM200	JM800
Madison Square	Felt	JM400, JM200	JM200	JM800
New Forest	Felt	JM400, JM200	JM200	JM800
Ocean Drive	Action Bac	JM400	-	JM800
Pagent	Action Bac	JM400	-	JM800
Palace	Action Bac	JM400	-	JM800
Rekord	Felt	JM400, JM200	JM200	JM800
Rutland	Felt	JM400, JM200	JM200	JM800
Seduction	Action Bac	JM400	-	JM800
Sophistication	Action Bac	JM400	-	JM800
Springdale Twist	Action Bac	JM400	-	JM800
Stainblock Range	Action Bac	JM400	-	JM800
Supreme Touch	Action Bac	JM400	-	JM800
Symphony	Action Bac	JM400	-	JM800
Vienna	Action Bac	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

INTERFACEFLOR • Tel 01274 690690 • Fax 01274 694095

A-Line	Graphlex	JM400	JM300	-
Acceleration	Graphlex	JM400	JM300	-
Accent Flanel	Graphlex	JM400	JM300	-
Adaptation	Graphlex	JM400	JM300	-
Aiki	Graphlex	JM400	JM300	-
Black & White	Graphlex	JM400	JM300	-
Blast from the Past	Graphlex	JM400	JM300	-
Chenille Warp	Graphlex	JM400	JM300	-
Circuit Board	Graphlex	JM400	JM300	-
Cubism	Graphlex	JM400	JM300	-
Dot Com	Graphlex	JM400	JM300	-
Duet	Graphlex	JM400	JM300	-
Elevation	Graphlex	JM400	JM300	-
Entropy	Graphlex	JM400	JM300	-
Equilibrium	Graphlex	JM400	JM300	-
Fastforward	Graphlex	JM400	JM300	-
Floorscope	Graphlex	JM400	JM300	-
Flor	Graphlar	JM400	JM300	-
Fluctuations	Graphlex	JM400	JM300	-
Foyer Barrier Tile	P V C	JM900	JM300	-
Furrows	Graphlex	JM400	JM300	-
Galleria Antron	GlasBac TM Vinyl	-	JM300	-
Galleria Wool / Nylon	GlasBac TM Vinyl	-	JM300	-
H350	Graphlex	JM400	JM300	-
H351	Graphlex	JM400	JM300	-
Heuga Range	Graphlex	JM400	JM300	-
Horizon	Graphlex	JM400	JM300	-
Intagilo	Graphlex	JM400	JM300	-
Lima	Graphlex	JM400	JM300	-
Linear Tonal	Graphlex	JM400	JM300	-
Menagerie	Graphlex	JM400	JM300	-
Merano	Graphlex	JM400	JM300	-
Metallic Weave	Graphlex	JM400	JM300	-
Mineral	Graphlex	JM400	JM300	-
Modernism	Graphlex	JM400	JM300	-
Nature Trails	Graphlex	JM400	JM300	-
New Horizons	Graphlex	JM400	JM300	-
Nylfloor Rib Sheet	Fibre bonded	JM400	-	JM800
Nylfloor Rib Tile	Graphlar	JM400	JM300	-
Nylfloor Velour Sheet	Fibre bonded	JM400	-	JM800
Nylfloor Velour Tile	Graphlar	JM400	JM300	-
Oblique	Graphlex	JM400	JM300	-
Orbit	Graphlex	JM400	JM300	-
Pallete 2000 Tile	GlasBac TM Vinyl	-	JM300	-
Pallete 3000 Tile	GlasBac TM Vinyl	-	JM300	-
Pallete 4000 Tile	GlasBac TM Vinyl	-	JM300	-
Polestar	Graphlex	JM400	JM300	-
Proportion	Graphlex	JM400	JM300	-
Rainforest	Graphlex	JM400	JM300	-
Sabi	Graphlex	JM400	JM300	-
Scandinavian Collection	Graphlex	JM400	JM300	-
Silk Route	Graphlex	JM400	JM300	-
Shadowland	Graphlex	JM400	JM300	-
Sherbert Fizz	Graphlex	JM400	JM300	-
Syncopation	Graphlex	JM400	JM300	-
Straightforward	Graphlex	JM400	JM300	-
Tapestry	Graphlex	JM400	JM300	-
Tatami	Graphlex	JM400	JM300	-
Tonal	Graphlex	JM400	JM300	-
Transcendent Collection	GlasBac TM Vinyl	-	JM300	-
Transformations	Graphlex	JM400	JM300	-
Veneer	Graphlex	JM400	JM300	-
Wabi Stripe / Weave	Graphlex	JM400	JM300	-
Woodland Way	Graphlex	JM400	JM300	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

INTERFLOOR LTD • Tel 01706 213131 • Fax 01706 224915

Duralay Durafit	Crumb Rubber	-	JM200	-
Duralay System Ten	Crumb Rubber	-	JM200	-
Tredaire Technics Range	Textron	-	JM200	-

JAYMART RUBBER AND PLASTICS LTD • Tel 01373 864926 • Fax 01373 858454

Apachestat	P V C	JM500, JM700	-	-
Astroturf CH4	Fibre	JM400, JM500	-	-
Boma Rips	Fibre bonded	JM400	-	-
Brushdown Coir	P V C	JM500, JM700	-	-
Ezyclean	P V C	JM500, JM700	-	-
Grasshopper	Latex	JM400	-	-
Limontamoquette	P V C	JM500, JM700	-	-
Mountain Grass	Latex	JM500, JM700	-	-
Poligras Decora	Latex	JM500, JM700	-	-
Polyrib	Latex	JM400	-	-
Raincheck Nylon Barrier Mat	P V C	JM500, JM700	-	-
Rushtik	Latex	JM400	-	-
Safe Deco	P V C / Cotton	JM500, JM700	-	-
Smart Textured Vinyl	P V C	JM500, JM700	-	-
Textra	Latex	JM500, JM700	-	-
Tufturf	Fibre bonded	JM400	-	-
Warcord	Latex	JM400	-	-
Zigazaga	Latex	JM400	-	-

JOSEPH HAMILTON AND SEATON LTD • Tel 01827 831400 • Fax 01827 831400

Tiles

Brindisi	Bitumen	JM400	JM300	-
Buffallo Mat	Bitumen	JM400	JM300	-
Cassini	Bitumen	JM400	JM300	-
Epsom	Bitumen	JM400	JM300	-
Linea	Eco Back	-	JM300	-
Matrix	Bitumen	JM400	JM300	-
Monza	Bitumen	JM400	JM300	-
Mutual	Bitumen	JM400	JM300	-
Pinstripe	Bitumen	JM400	JM300	-
Postino	Bitumen	JM400	JM300	-
Random	Eco Back	-	JM300	-
Rimini	Bitumen	JM400	JM300	-
Roma	Bitumen	JM400	JM300	-
Sicily	Bitumen	JM400	JM300	-
Sorrento	Bitumen	JM400	JM300	-
Sprint	Bitumen	JM400	JM300	-
Taranto	Bitumen	JM400	JM300	-
Tretford Carpet Tile	P V C	-	JM300	-
Turin	Bitumen	JM400	JM300	-
Verona Plus	Bitumen	JM400	JM300	-

Sheet

Albatross II	Secondary	JM400	-	JM800
Armitage	Secondary	JM400	-	JM800
Ballentrae Classic	Secondary	JM400	-	JM800
Banff Design	Secondary	JM400	-	JM800
Bull Dog Mat	Latex	JM900	-	-
Capital City	Secondary	JM400	-	JM800
Chepstow	Permafresh Contract	JM400, JM200	JM200	JM800
City Style	Felt	JM400, JM200	JM200	JM800
Commissionaire II	Secondary	JM400	-	JM800
Como II	Latex	JM900	-	-
Design Creations	Secondary	JM400	-	JM800
Dino-Mat	P V C	JM900	-	-
Dorchester	Secondary	JM400	-	JM800
Elder	Secondary	JM400	-	JM800
Epsom	Secondary	JM400	-	JM800
Esprit II	Secondary	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Format	Secondary	JM400	-	JM800
Fortis	Secondary	JM400	-	JM800
Frontier	Woven Synthetic	JM400, JM200	JM200	JM800
Handsacre II	Secondary	JM400	-	JM800
Hawthorn II	Secondary	JM400	-	JM800
Haywood	Secondary	JM400	-	JM800
Hedgerow	Secondary	JM400	-	JM800
Hornbeam	Permafresh Contract	JM400, JM200	JM200	JM800
Hospi-Classic II	Impervious	JM400, JM200	-	*
Hospi-Classic Plain	Impervious	JM400, JM200	-	*
Hospi-Comfort	Impervious	JM400, JM200	-	*
Hospi-Elite	Impervious	JM400, JM200	-	*
Hospi-Flair	Impervious	JM400, JM200	-	*
Hospi-Guard II	Impervious	JM400, JM200	-	*
Hospi-Loop II	Impervious	JM400, JM200	-	*
Hospi-Lux	Impervious	JM400, JM200	-	*
Hospi-Premier	Impervious	JM400, JM200	-	*
Hospi-Style	Impervious	JM400, JM200	-	*
Hospi-Super	Impervious	JM400, JM200	-	*
Hospi-Supreme	Impervious	JM400, JM200	-	*
Hospi-Tones	Impervious	JM400, JM200	-	*
Hospi-Twist	Impervious	JM400, JM200	-	*
Hospi-Twist Heathers	Impervious	JM400, JM200	-	*
Matrix	Secondary	JM400	-	JM800
Metropol	Secondary	JM400	-	JM800
Milan Lite	Felt	JM400, JM200	JM200	JM800
Milan Plus	Permafresh Contract	JM400, JM200	JM200	JM800
Modern Edge	Secondary	JM400	-	JM800
New Garda	Secondary	JM400	-	JM800
Newbury	Secondary	JM400	-	JM800
Omega	Secondary	JM400	-	JM800
Ottawa	Secondary	JM400	-	JM800
Palmera	Secondary	JM400	-	JM800
Panama II	Secondary	JM400	-	JM800
Petra	Felt	JM400, JM200	JM200	JM800
Plaza	Secondary	JM400	-	JM800
Principle	Felt	JM400, JM200	JM200	JM800
Rhino-Mat	P V C	JM900	-	-
Roma	Felt	JM400, JM200	JM200	JM800
Savoy	Secondary	JM400	-	JM800
Senior	Felt	JM400, JM200	JM200	JM800
Stanford II	Secondary	JM400	-	JM800
Town House	Felt	JM400, JM200	JM200	JM800
Tretford	Hessian	JM400	-	JM800
Trio Mat	Latex	JM900	-	-
Tutor	Felt	JM400, JM200	JM200	JM800
Vancouver	Secondary	JM400	-	JM800
Verona	Secondary	JM400	-	JM800
Whittington Twist 30 / 40 / 50	Jute	JM400	-	JM800

* for vertical bonds please refer to our technical department

KERSAINT COBB AND CO LTD • Tel 01675 430430 • Fax 01675 430222

Natural Flooring Range

Coir Range	Latex Foam	JM400	-	JM800
Fine Sea Grass Range	Latex Foam	JM400	-	JM800
Jute Range	Latex Foam	JM400	-	JM800
Mountain Grass Range	Latex Foam	JM400	-	JM800
Sea Grass Range	Latex Foam	JM400	-	JM800
Sisal Range	Latex Foam	JM400	-	JM800

Wool Range

3 Rib	Jute	JM400	-	JM800
Beach Hut	Jute	JM400	-	JM800
Chic Living	Jute	JM400	-	JM800
Chic Style	Jute	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Chunky Rib	Jute	JM400	-	JM800
Marble	Jute	JM400	-	JM800
Mountain	Jute	JM400	-	JM800
Natural Weave	Jute	JM400	-	JM800
Pampas Berber	Jute	JM400	-	JM800
Pampas Boucle	Jute	JM400	-	JM800
Pampas Bubbles	Jute	JM400	-	JM800
Pampas Fine Rib	Jute	JM400	-	JM800
Pampas Heaven	Jute	JM400	-	JM800
Pampas Herringbone	Jute	JM400	-	JM800
Pampas Knitted	Jute	JM400	-	JM800
Pampas Kronos	Jute	JM400	-	JM800
Pampas Lattice	Jute	JM400	-	JM800
Pampas Nabou	Jute	JM400	-	JM800
Pampas Palazzo	Jute	JM400	-	JM800
Pampas Rainbow	Jute	JM400	-	JM800
Pampas Tivoli	Jute	JM400	-	JM800
Pique	Jute	JM400	-	JM800
Savannah Range	Jute	JM400	-	JM800
Vineyard	Jute	JM400	-	JM800

KINGSMEAD CARPETS LTD • Tel 01827 831424 • Fax 01827 831425

Argyll	Secondary	JM400, JM200	JM200	JM800
Artwork	Secondary	JM400, JM200	JM200	JM800
Ayrshire	Secondary	JM400, JM200	JM200	JM800
Cheviot	Secondary & Felt	JM400, JM200	JM200	JM800
Enjoyment	Secondary & Felt	JM400, JM200	JM200	JM800
Everglade	Secondary	JM400, JM200	JM200	JM800
Gallantry	Felt	JM400, JM200	JM200	JM800
Home	Secondary	JM400, JM200	JM200	JM800
House	Secondary	JM400, JM200	JM200	JM800
In The Groove	Secondary	JM400, JM200	JM200	JM800
Leader	Secondary	JM400, JM200	JM200	JM800
Lothian	Secondary	JM400, JM200	JM200	JM800
Motivator	Secondary	JM400, JM200	JM200	JM800
New Vitronic	Secondary	JM400, JM200	JM200	JM800
Paloma	Secondary	JM400, JM200	JM200	JM800
Rapport	Secondary	JM400, JM200	JM200	JM800
Shaggy Dog	Secondary	JM400, JM200	JM200	JM800
Stoney Ground	Secondary & Felt	JM400, JM200	JM200	JM800
Wik-Kid	Secondary	JM400, JM200	JM200	JM800
Wow	Felt	JM400, JM200	JM200	JM800

LANO NV BELGIUM • Tel 0032 56654000 • Fax 0032 56654009

Adagio	Textile	JM400	-	JM800
Agrest SB	Woven Scrim	JM400, JM200	JM200	JM800
Arena AB	Woven Scrim	JM400, JM200	JM200	JM800
Bolero S	Felt	JM400, JM200	JM200	JM800
Cancun	Woven Scrim	JM400, JM200	JM200	JM800
Castello FB	X-traback	JM400	-	JM800
Comtessa SB / DL	Woven Scrim	JM400, JM200	JM200	JM800
Coral Cove	Woven Scrim	JM400, JM200	JM200	JM800
Corindo SB	Woven Scrim	JM400, JM200	JM200	JM800
Corona	Woven Scrim	JM400, JM200	JM200	JM800
Corona	X-traback	JM400	-	JM800
Garden	Latex	JM400	-	JM800
Granit AB	Woven Scrim	JM400, JM200	JM200	JM800
Havanna AB	Woven Scrim	JM400, JM200	JM200	JM800
Heathertwist AB	Woven Scrim	JM400, JM200	JM200	JM800
Heathertwist Supreme AB	Woven Scrim	JM400, JM200	JM200	JM800
Impala SB / DL	Woven Scrim	JM400, JM200	JM200	JM800
Inspirations AB	Woven Scrim	JM400, JM200	JM200	JM800
Inspirations Supreme AB	Woven Scrim	JM400, JM200	JM200	JM800
Lanotwist AB	Woven Scrim	JM400, JM200	JM200	JM800
Limbo	Textile	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Mambo AB	Woven Scrim	JM400, JM200	JM200	JM800
Matrix Tile Range	Bitumen / Fleece	JM400	JM300	-
Mayfair Velvet SB	Woven Scrim	JM400, JM200	JM200	JM800
Mirador	Woven Scrim	JM400, JM200	JM200	JM800
Natural Elements	Woven Scrim	JM400, JM200	JM200	JM800
Noblesse KT	Textile	JM400	-	JM800
Oasis	Woven Scrim	JM400, JM200	JM200	JM800
Opal	Woven Scrim	JM400, JM200	JM200	JM800
Orion	Woven Scrim	JM400, JM200	JM200	JM800
Parma AB	Woven Scrim	JM400, JM200	JM200	JM800
Parma PF	Latex Foam	JM400, JM200	-	JM800
Pembridge Twist AB	Woven Scrim	JM400, JM200	JM200	JM800
Reatta	Woven Scrim	JM400, JM200	JM200	JM800
Retro AB	Woven Scrim	JM400, JM200	JM200	JM800
Riviera AB	Woven Scrim	JM400, JM200	JM200	JM800
Royal Broadloom	Woven	JM400, JM200	JM200	JM800
Royal Jubilee	Woven	JM400, JM200	JM200	JM800
Royal Pavilion	Woven	JM400, JM200	JM200	JM800
Rustic Berber AB	Woven Scrim	JM400, JM200	JM200	JM800
Rustic Sensations AB	Woven Scrim	JM400, JM200	JM200	JM800
Scala IB	Embossed Foam	JM400, JM200	-	JM800
Shetland Textures	Woven Scrim	JM400, JM200	JM200	JM800
Splendid KT	Textile	JM400	-	JM800
Square AB	Woven Scrim	JM400, JM200	JM200	JM800
Sweet	Latex Foam	JM400, JM200	-	JM800
Twilight AB	Woven Scrim	JM400, JM200	JM200	JM800
Twilight Bath	Waffle	JM400	-	JM800
Twilight FB	X-traback	JM400	-	JM800
Versailles	Woven	JM400, JM200	JM200	JM800
Woolclass SB / DL	Woven Scrim	JM400, JM200	JM200	JM800
X-tratwist FB	X-traback	JM400	-	JM800
Zen Design SB	Woven Scrim	JM400, JM200	JM200	JM800
Zen SB	Woven Scrim	JM400, JM200	JM200	JM800

LECAFLOR LTD • Tel 01845 577522 • Fax 01845 577193

Basket Weave	Jute	JM400	-	JM800
Boucle	Latex	JM400	-	-
Bronze Age	Textile	JM400	-	JM800
Bullrush	Felt & Latex Foam	JM400	-	JM800
Buttermere	Action Bac	JM400, JM200	JM200	JM800
Cornerstone	Action Bac	JM400, JM200	JM200	JM800
Cornfields	Jute	JM400	-	JM800
Cosmo Sisal	Latex	JM400	-	-
Country Days IV	Jute	JM400	-	JM800
Crete	Jute	JM400	-	JM800
Crofters Choice	Jute	JM400	-	JM800
Design Weave II	Action Bac	JM400, JM200	JM200	JM800
Falklands	Jute	JM400	-	JM800
Guardian 2000 & Stipple	Action Bac	JM400, JM200	JM200	JM800
Hambleton	Jute	JM400	-	JM800
Herringbone	Latex	JM400	-	-
Hersea	Latex	JM400	-	-
Hospitality Q	Action Bac	JM400, JM200	JM200	JM800
Intercity Tile	Bitumen / Felt	JM400	JM300	-
Jura	Action Bac	JM400, JM200	-	JM800
Millenium Q	Action Bac	JM400, JM200	JM200	JM800
Monet	Latex Foam	JM400	-	JM800
Nautilus	Action Bac	JM400, JM200	JM200	JM800
New Granary	Jute	JM400	-	JM800
Oasis	Latex Foam	JM400	-	JM800
Panama Coir	Latex	JM400	-	-
Panama Seagrass	Latex	JM400	-	-
Patagonia	Latex Foam	JM400	-	JM800
Persian Lamb	Action Bac	JM400, JM200	JM200	JM800
Predator Loop	Bitumen / Felt	JM400	JM300	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Predator Velour	Bitumen / Felt	JM400	JM300	-
Premier	Textile	JM400, JM200	JM200	JM800
Quattro	Latex	JM400	-	-
Quattro Carpet tile	Bitumen	JM400	JM300	-
Rainbow	Latex	JM400	-	-
Raphael	Textile	JM400, JM200	JM200	JM800
Ridgestone II	Action Bac	JM400, JM200	JM200	JM800
Rustic Weave	Jute	JM400	-	JM800
Santo Sisal	Latex	JM400	-	-
Savannah	Action Bac	JM400, JM200	JM200	JM800
Sico	Latex	JM400	-	-
Tampico Sisal	Latex	JM400	-	-
Texel	Action Bac	JM400, JM200	JM200	JM800
Tigro Sisal	Latex	JM400	-	-
Touchstone	Action Bac	JM400, JM200	JM200	JM800
Tudor Court	Textile	JM400	-	JM800
Tweedswood II	Jute	JM400	-	JM800
Waterford	Action Bac	JM400, JM200	JM200	JM800
Wexford	Jute	JM400	-	JM800

LEIGH SPINNERS LTD • Tel 01942 673232 • Fax 01942 261694

Atlas Tile	Bitumen	JM400	JM300	-
Atlas Rib	Fibrebonded	JM400	-	JM800
Atlas Velour	Fibrebonded	JM400	-	JM800
Canyon Entrance Matting	Embossed Gel Foam	JM900	-	JM800
Hercules	Embossed Gel Foam	JM400	-	JM800
Romulus	Embossed Gel Foam	JM400	-	JM800
Samson Contract Rib	Embossed Gel Foam	JM400	-	JM800
Samson Contract Velour	Embossed Gel Foam	JM400	-	JM800
Vulcan Contract Tile	Bitumen	JM400	JM300	-
Vulcan Rib	Fibrebonded	JM400	-	JM800
Vulcan Velour	Fibrebonded	JM400	-	JM800

LITTNER HAMPTON LTD • Tel 0208 5208474 • Fax 0208 5204464

Contract Cord	Jute Hessian	JM400	-	JM800
Colourpoint	Jute Hessian	JM400	-	JM800
Country Charm	Jute Hessian	JM400	-	JM800
Country Square	Jute Hessian	JM400	-	JM800
Crofter	Jute Hessian	JM400	-	JM800
Denby	Jute Hessian	JM400	-	JM800
Elite Supertwist / Twist	Action Bac	JM400	-	JM800
Florida	Felt	JM400, JM200	JM200	JM800
Grosvenor Square	Jute Hessian	JM400	-	JM800
Jaipur Cord	Jute Hessian	JM400	-	JM800
Knossos	Jute Hessian	JM400	-	JM800
Kos	Jute Hessian	JM400	-	JM800
Linea Broadloom	Jute Hessian	JM400	-	JM800
Linz Berber	Action Bac	JM400	-	JM800
Memphis	Felt	JM400	JM200	JM800
Mirage	Jute Hessian	JM400	-	JM800
Monique	Jute Hessian	JM400	-	JM800
Montego	Jute Hessian	JM400	-	JM800
Natural Inspirations	Jute Hessian	JM400	-	JM800
New Boucle	Jute Hessian	JM400	-	JM800
Park Avenue	Action Bac	JM400	-	JM800
Perth Berber	Jute Hessian	JM400	-	JM800
Regatta	Action Bac	JM400	-	JM800
Regatta	Gel	JM400	-	JM800
Rustic Basket	Jute Hessian	JM400	-	JM800
Rustic Loop	Action Bac	JM400	-	JM800
Rustic Twist	Jute Hessian	JM400	-	JM800
Rustic Weave	Jute Hessian	JM400	-	JM800
Stratford Supertwist	Jute Hessian	JM400	-	JM800
Stratford Supreme Twist	Action Bac	JM400	-	JM800
Stratford Twist	Jute Hessian	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

Supreme Saxony	Jute Hessian	JM400	-	JM800
Tailored Beauty	Action Bac	JM400	-	JM800
Zealandia	Jute Hessian	JM400	-	JM800

WILLIAM LOMAS CARPETS LTD • Tel : 0845 6528811 • Fax : 0845 6528822

William Loop	Jute Hessian	JM400	-	JM800
William Twist	Jute Hessian	JM400	-	JM800
William Velvet	Jute Hessian	JM400	-	JM800
William Stripe	Jute Hessian	JM400	-	JM800

LSI OVATION FLOORING LTD • Tel 01457 810987 • Fax 01457 810940

Antique Wood	P V C	JM500, JM700	-	-
Birds Eye Maple	P V C	JM500, JM700	-	-
Clovelly	P V C	JM500, JM700	-	-
Concrete	P V C	JM500, JM700	-	-
Cottage Grain	P V C	JM500, JM700	-	-
Elements	P V C	JM500, JM700	-	-
Euromarble	P V C	JM500, JM700	-	-
Granite	P V C	JM500, JM700	-	-
Hammered Aluminium	P V C	JM500, JM700	-	-
Imagination Collection	P V C	JM500, JM700	-	-
Leather	P V C	JM500, JM700	-	-
Natural Wood Collection	P V C	JM500, JM700	-	-
Shale	P V C	JM500, JM700	-	-
Slate	P V C	JM500, JM700	-	-
Sparkly Chips	P V C	JM500, JM700	-	-
Treadplate	P V C	JM500, JM700	-	-
Wood Collection	P V C	JM500, JM700	-	-

MARLINGS LTD • Tel 01453 821800 • Fax 01453 791167

See Warlord Carpets

MAYFIELD CARPETS LTD. • Tel 01706 639866 • Fax 01706 658758

Arcadia	Jute Hessian	JM400, JM200	JM200	JM800
Borrowdale Elite	Jute Hessian	JM400, JM200	JM200	JM800
Borrowdale Supreme	Jute Hessian	JM400, JM200	JM200	JM800
Mayfield Natural Collection	Jute Hessian	JM400, JM200	JM200	JM800
Mayfield Twist Choice	Jute Hessian	JM400, JM200	JM200	JM800
Mayfield Twist Select	Jute Hessian	JM400, JM200	JM200	JM800
Rydal Twist	Jute Hessian	JM400, JM200	JM200	JM800
Stratford	Jute Hessian	JM400, JM200	JM200	JM800
Super Maxim	Jute Hessian	JM400, JM200	JM200	JM800

MERCADO CARPETS • Tel 0113 3802900 • Fax 0133 3802828

See Alvin Morris

MILLIKEN CONTRACT CARPETS • Tel 01942 826073 • Fax 01942 826570

Carpet Tiles

Essentials Value Tufted Loop Pile	Polyurethane Foam	JM500, JM700	JM300	JM800
Grand Plaza	Polyurethane Foam	JM500, JM700	JM300	JM800
High Performance Loop pile	Polyurethane Foam	JM500, JM700	JM300	JM800
Luxury Textured Loop Pile	Polyurethane Foam	JM500, JM700	JM300	JM800
Milliken Colours	Fibre Glass / P V C	-	JM300	-
Milliken Tweeds	Fibre Glass / P V C	-	JM300	-
Premium Cut Pile Fusion Bonded	Polyurethane Foam	JM500, JM700	JM300	JM800
Tufted Textured Loop Pile	Polyurethane Foam	JM500, JM700	JM300	JM800

MOHAWK INDUSTRIES • Tel 01282 606992 • Fax 01282 606995

Bigelow Broadloom- Range	Action Bac	JM400	JM200	JM800
Bigelow Broadloom- Range	Unitary Plus	JM400	JM200	JM800
Bigelow Broadloom- Range	UPS	JM400, JM200	JM200	JM800
Bigelow Broadloom- Range	Woven	JM400	JM200	JM800
Bigelow Modular - Range	EcoFlex	-	JM300	-
Bigelow Modular - Range	P V C	-	JM300	-
Les Broadloom	Unibond	JM400	JM200	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Karastan & Durkan Commercial - Range	Unitary Plus	JM400	JM200	JM800
Karastan & Durkan Commercial - Range	UPS	JM400, JM200	JM200	JM800
Karastan & Durkan Modular - Range	Woven	JM400	JM200	JM800
Durkan Modular - Range	P V C	-	JM300	-
Lees Modular	Thermoplastic	-	JM300	-
MORLEYS LTD • Tel 01772 626700 • Fax 01772 627372				
Aluminium Stair Edgings	-	A2, A17	-	-
Aluminium Stair Nosings	-	A2, A17	-	-
Aluminium Stair Trims	-	A2, A17	-	-
PVC Bevel Edges	-	JM800	JM300	JM800
PVC Capping	-	JM800	JM300	JM800
PVC Coveformer	-	JM800	JM300	JM800
PVC Skirtings	-	JM800	JM300	JM800
uPVC Stair Edgings	-	A2, A17	-	-
uPVC Stair Nosings	-	A2, A17	-	-
uPVC Stair Trims	-	A2, A17	-	-
Entrance Matting				
Cocomor	Waffle	JM900	-	JM800
Combi-Tread	P V C	JM900	-	JM800
Dirtwebb 9mm	P V C	JM900	-	JM800
Endura	Fibrebonded	JM900	-	JM800
Fortress	Waffle	JM900	-	JM800
Fortress Flame Retardant	Fibrebonded	JM900	-	JM800
Hurricane	P V C	JM900	-	JM800
Invincible	Fibrebonded	JM900	-	JM800
Tornado	Fibrebonded	JM900	-	JM800
Valiant	Fibrebonded	JM900	-	JM800
Vortex	P V C	JM900	-	JM800
Tiles				
Endura	Bitumen / Felt	JM900	JM300	JM800
Fortress	Bitumen / Felt	JM900	JM300	JM800
NAVAN CARPETS LTD • Tel 00353 15052200 • Fax 00353 15052288				
Abbey Twist	Felt	JM400	-	JM800
Carlton Hall	Woven	JM400	-	JM800
Carra Wool	Jute Hessian	JM400	-	JM800
Elegance	Jute Hessian	JM400	-	JM800
Marfield	Woven	JM400	-	JM800
Navan Diamond	Woven	JM400	-	JM800
Trinity Twist	Jute Hessian	JM400	-	JM800
Graphic Combinations S	Jute	JM400, JM200	JM200	JM800
Graphic Combinations S	Unitary	JM400	-	JM800
Quadrangle	Felt	JM400, JM200	JM200	JM800
Quadrangle	Gel Foam	JM400	-	JM800
Quadrangle	Jute	JM400, JM200	JM200	JM800
Quadrangle	Unitary	JM400	-	JM800
Colortech Contract				
Custom Range	Felt	JM400, JM200	JM200	JM800
Custom Range	Gel Foam	JM400	-	JM800
Custom Range	Jute	JM400, JM200	JM200	JM800
Custom Range	Unitary	JM400	-	JM800
Carpet Tiles				
Custom Tiles	Bitumen	JM400	JM300	-
OBJECT CARPETS (UK) LTD • Tel 01580 852585 • Fax 01580 852586				
Sheet				
Full Range	Action Bac	JM400, JM200	JM200	JM800
Full Range	Synthetic Felt	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

Tiles

Sl. Contract	Bitumen / Felt	JM400	JM300	-
Sl. Cord	Bitumen / Felt	JM400	JM300	-
Sl. Fishbone	Bitumen / Felt	JM400	JM300	-
Sl. Madra	Bitumen / Felt	JM400	JM300	-
Sl. Nyloop	Bitumen / Felt	JM400	JM300	-
Sl. Nylrips	Bitumen / Felt	JM400	JM300	-
Sl. Nyltecc	Bitumen / Felt	JM400	JM300	-
Sl. Poodle	Bitumen / Felt	JM400	JM300	-
Sl. Punto	Bitumen / Felt	JM400	JM300	-
Sl. Python	Bitumen / Felt	JM400	JM300	-
Sl. Rondo	Bitumen / Felt	JM400	JM300	-
Sl. Springles	Bitumen / Felt	JM400	JM300	-
Sl. Leo	Bitumen / Felt	JM400	JM300	-

OVATION INTERIOR FLOORING DESIGN LTD • Tel 01457 810987 • Fax 01457 810940

See LSI Ovation Flooring Ltd

JOHN PALMER CARPETS • Tel 01329 221933 • Fax 01329 230780

Campus	Latex Foam - Embossed	JM400, JM200	-	JM800
Castelano	Jute	JM400, JM200	JM200	JM800
Desert Twist	Action Bac	JM400, JM200	JM200	JM800
Eclipse Elite	Hessian	JM400	-	JM800
Everest	Latex Foam - Comp	JM400	-	JM800
Fiesta	Action Bac	JM400, JM200	JM200	JM800
Gala	Gel	JM400	-	JM800
Gala	Action Bac	JM400, JM200	JM200	JM800
Gala	Felt	JM400, JM200	JM200	JM800
Grampian	Latex Foam - Comp	JM400	-	JM800
Graphics Collection	Hessian	JM400	-	JM800
Heathertwist	Jute	JM400, JM200	JM200	JM800
Heathertwist Supreme	Jute	JM400, JM200	JM200	JM800
Paragon	Latex Foam - Embossed	JM400, JM200	-	JM800
Penbridge Twist	Action Bac	JM400, JM200	JM200	JM800
Prestige Berber Twist	Action Bac	JM400, JM200	JM200	JM800
Prestige Twist	Action Bac	JM400, JM200	JM200	JM800
Sandringham 30oz, 40oz, & 50oz	Hessian	JM400	-	JM800
Shepherd Twist	Action Bac	JM400, JM200	JM200	JM800
Startwist II	Jute	JM400, JM200	JM200	JM800
Startwist II Supreme	Jute	JM400, JM200	JM200	JM800
Twilight AB	Woven Scrim	JM400, JM200	JM200	JM800
Twilight Bath	Waffle	JM400	-	JM800
Twilight FB	X-traback	JM400	-	JM800
Verona Stripe	Jute	JM400, JM200	JM200	JM800
Vitory Cord	Gel	JM400	-	JM800

PARAGON BY HECKMONDWIKE • Tel 0845 6010431 • Fax 0800 7314521

Tiles

Ashbury	Bitumen	JM400	JM300	-
Colourquest	Bitumen	JM400	JM300	-
Distinction	Bitumen	JM400	JM300	-
Ferrara	Bitumen	JM400	JM300	-
Macaw	Bitumen	JM400	JM300	-
Maestro	Bitumen	JM400	JM300	-
Navigator Plus	Bitumen	JM400	JM300	-
Oriental Collection	Bitumen	JM400	JM300	-
Parallel Lines / Reflections	Bitumen	JM400	JM300	-
Sirocco	Bitumen	JM400	JM300	-
Toccarre	Bitumen	JM400	JM300	-
Workspace	Bitumen	JM400	JM300	-

Sheet

Harmonise	Woven	JM400, JM200	JM200	JM800
Toscana	Textile	JM400, JM200	JM200	JM800
Entrance Master	Latex Foam	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Multiplicity	Impervious Foam	JM400	-	JM800
Phenomenon	Woven	JM400, JM200	JM200	JM800
PENTHOUSE CARPETS LTD • Tel 01706 341231 • Fax 01706 860577				
Carlton Twist	Jute Hessian	JM400, JM200	JM200	JM800
Country Berber	Jute Hessian	JM400, JM200	JM200	JM800
Country Tweed	Jute Hessian	JM400, JM200	JM200	JM800
Esprit	Jute Hessian	JM400, JM200	JM200	JM800
Maple	Jute Hessian	JM400, JM200	JM200	JM800
Pentwist 40	Jute Hessian	JM400, JM200	JM200	JM800
Pentwist 50	Jute Hessian	JM400, JM200	JM200	JM800
Pennine Heather Collection	Jute Hessian	JM400, JM200	JM200	JM800
Pennine Plain Collection	Jute Hessian	JM400, JM200	JM200	JM800
Pinaster	Jute Hessian	JM400, JM200	JM200	JM800
Pinnacle	Jute Hessian	JM400, JM200	JM200	JM800
Stateside 40	Jute Hessian	JM400, JM200	JM200	JM800
Stateside 50	Jute Hessian	JM400, JM200	JM200	JM800
Super Carlton Twist	Jute Hessian	JM400, JM200	JM200	JM800
Trade Winds	Jute Hessian	JM400, JM200	JM200	JM800
Vantage 50	Jute Hessian	JM400, JM200	JM200	JM800
Vantage 60	Jute Hessian	JM400, JM200	JM200	JM800
Vermont 40	Jute Hessian	JM400, JM200	JM200	JM800
Vermont 50	Jute Hessian	JM400, JM200	JM200	JM800
PLAY - RITE LTD • Tel 01924 412488 • Fax 01924 412337				
Claytex	Fibrebonded	JM400	-	-
Quick-Court	Fibrebonded	JM400	-	-
POLYFLOR LTD • Tel 0161 767 1111 • Fax 0161 767 1100				
Vinyl to EN649				
Bevel Line	Vinyl	JM700	-	*
Camaro PU	Vinyl	JM700	-	*
Colonia	Vinyl	JM700	-	*
Expona Domestic PU	Vinyl	JM700	-	*
Expona PU	Vinyl	JM700	-	*
Forest fx	Vinyl	JM500	-	*
Kudos PU	Vinyl	JM700	-	*
Polyflex Plus Tiles	Vinyl	JM500, JM700	-	*
Polyflor 2000 PUR	Vinyl	JM500, JM700	-	*
Polyflor Classic Mystique PUR	Vinyl	JM500, JM700	-	*
Polyflor Forest FX Acoustic	P V C Foam	JM500, JM700	-	*
Polyflor Gallery FX Acoustic	P V C Foam	JM500, JM700	-	*
Polyflor Mystique PUR	Vinyl	JM500, JM700	-	*
Polyflor Prestige PUR	Vinyl	JM500, JM700	-	*
Polyflor Sport 67	Vinyl Foam	JM500, JM700	-	*
Polyflor Sport 80	Vinyl Foam	JM500, JM700	-	*
Polyflor XL PU	Vinyl	JM500, JM700	-	*
Polyflor XL Standard	Vinyl	JM500, JM700	-	*
Polysafe 3.5	Vinyl	JM500, JM700	-	*
Polysafe Astral	Vinyl	JM500, JM700	-	*
Polysafe Corona	Vinyl	JM500, JM700	-	*
Polysafe Hydro	Vinyl	JM500, JM700	-	*
Polysafe Mosaic	Vinyl	JM500, JM700	-	*
Polysafe Standard	Vinyl	JM500, JM700	-	*
Polysafe Strata	Vinyl	JM500, JM700	-	*
Polysafe Ultima	Vinyl	JM500, JM700	-	*
Polysafe Vogue Ultra	Vinyl	JM500, JM700	-	*
Polysafe Wood FX	Vinyl	JM500, JM700	-	*
Polysafe Wood FX Acoustic	P V C Foam	JM500, JM700	-	*
Stone FX	Vinyl	JM500, JM700	-	*
Accessories				
Polyflor Ejecta	P V C	-	-	JM800
Polytred Acoustifoam	Vinyl Foam	JM500	-	-

* for vertical bonds please refer to our technical department

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

WILLIAM POWNALL AND SONS LTD • Tel 01706 716014 • Fax 01706 649002

Comfort	Jute Hessian	JM400, JM200	-	JM800
Fenland Berbers	Jute Hessian	JM400, JM200	-	JM800
Fenland Loop	Jute Hessian	JM400, JM200	-	JM800
Fenland Textures	Jute Hessian	JM400, JM200	-	JM800
Fenland Twist	Jute Hessian	JM400, JM200	-	JM800
Graphics Collection	Jute Hessian	JM400, JM200	-	JM800

RAWSONS CARPETS LTD • Tel 01924 382860 • Fax 01924 366204

Tiles

Calder	Bitumen / Felt	JM400	JM300	-
Castle	Bitumen / Felt	JM400	JM300	-
Champion	Bitumen / Felt	JM400	JM300	-
Dominator Plus	Bitumen / Felt	JM400	JM300	-
Eden	Bitumen / Felt	JM400	JM300	-
Eurocord 2000	Bitumen / Felt	JM400	JM300	-
Felkirk	Bitumen / Felt	JM400	JM300	-
Freeway	Bitumen / Felt	JM400	JM300	-
Fresca	Bitumen / Felt	JM400	JM300	-
Primary Colours	Bitumen / Felt	JM400	JM300	-
Rivera	Bitumen / Felt	JM400	JM300	-
Spectus	Bitumen / Felt	JM400	JM300	-
Spikemaster	Bitumen / Felt	JM400	JM300	-
Starquest Cut Pile	Bitumen / Felt	JM400	JM300	-
Starquest Loop Pile	Bitumen / Felt	JM400	JM300	-

Sheet

Champion	Fibrebonded	JM400	-	JM800
Denby	Fibrebonded	JM400	-	JM800
Dominator Plus	Latex Waffle	JM400	-	JM800
Eurocord 2000	Fibrebonded	JM400	-	JM800
Felkirk	Fibrebonded	JM400	-	JM800
Freeway	Fibrebonded	JM400	-	JM800
Fresca	Latex Waffle	JM400	-	JM800
Hercules	Latex Waffle	JM400	-	JM800
Patio	Fibrebonded	JM400	-	JM800
Primary Colours	Fibrebonded	JM400	-	JM800
Trackmaster	Latex Waffle	JM400	-	JM800

RYALUX CARPETS LTD • Tel : 01706 716014 • Fax : 01706 649002

Desert Tones	Jute Hessian	JM400	-	JM800
Natural Twist	Jute Hessian	JM400	-	JM800
New Ryalux	Jute Hessian	JM400	-	JM800
New Ryatwist Tweed	Jute Hessian	JM400	-	JM800
Ryadream	Jute Hessian	JM400	-	JM800
Ryasax	Jute Hessian	JM400	-	JM800
Ryasilk	Jute Hessian	JM400	-	JM800
Ryasilk Twist	Jute Hessian	JM400	-	JM800
Ryatwist Tweed Collection	Jute Hessian	JM400	-	JM800
Ryavelvet Royale	Jute Hessian	JM400	-	JM800
Ryaweave Natural Collection	Jute Hessian	JM400	-	JM800
Shoretone	Jute Hessian	JM400	-	JM800
Simply Loops	Jute Hessian	JM400	-	JM800
Simply Velvet	Jute Hessian	JM400	-	JM800
The Studio Collection	Jute Hessian	JM400	-	JM800
Ultimate	Jute Hessian	JM400	-	JM800
Urban Naturals	Jute Hessian	JM400	-	JM800
V&A Periodtwist	Jute Hessian	JM400	-	JM800
V&A Periodvelvet	Jute Hessian	JM400	-	JM800
V&A Ryatwist Colour Collection	Jute Hessian	JM400	-	JM800
V&A Twist	Jute Hessian	JM400	-	JM800

SCATCHARD CARPETS • Tel 01924 402051 • Fax 01924 406515

Counrty Life	Jute Hessian	JM400	-	JM800
Fairway Collection	Jute Hessian	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Fine Heritage Twist	Jute Hessian	JM400	-	JM800
Fine Heritage Twist	Unitary	JM400	-	JM800
Super Fine Heritage Twist	Jute Hessian	JM400	-	JM800
Super Fine Heritage Twist	Unitary	JM400	-	JM800

SCOTMAT LTD • Tel 01506 859995 • Fax 01506 859996

Atlantis	Impervious Foam	JM400, JM200	-	JM800
Aztec	Action Bac	JM400, JM200	JM200	JM800
Cairngorm	Impervious Foam	JM400, JM200	-	JM800
Capital Twist	Jute Hessian	JM400	-	JM800
Cascade	Action Bac	JM400, JM200	JM200	JM800
Glen Royale	Action Bac	JM400, JM200	JM200	JM800
Heathertred	Action Bac	JM400, JM200	JM200	JM800
Microcord	Fibre bonded	JM400	-	JM800
Pixel	Impervious Unitary	JM400	-	JM800
Quasar	Action Bac	JM400, JM200	JM200	JM800
Scotrib	Fibre bonded	JM400	-	JM800
Sprint Action	Action Bac	JM400, JM200	JM200	JM800
Western Glen	Jute Hessian	JM400	-	JM800
Western Isles	Unitary	JM400	-	JM800

Tiles

Cairngorm	Bitumen	JM400	JM300	-
Cobra	Bitumen	JM400	JM300	-
Glen Royale	Bitumen	JM400	JM300	-
Heathertred	Bitumen	JM400	JM300	-
Magma	Bitumen	JM400	JM300	-
Meteor	Bitumen	JM400	JM300	-
Pixel	Bitumen	JM400	JM300	-
Quasar	Bitumen	JM400	JM300	-
Toledo	Bitumen	JM400	JM300	-
Western Glen	Bitumen	JM400	JM300	-

BRUCE STARKE & CO. LTD • Tel 01379 870209 • Fax 01379 871232

Sheet

Dartmoor	Fibrebonded	JM400	-	JM800
Fairisle	Latex Foam - Comp	JM400	-	JM800
Hebrides	Latex Foam - Comp	JM400	-	JM800
Interiguard	Nitrile	JM400	-	JM800
Malin	Latex Foam - Comp	JM400	-	JM800
Orkney	Latex Foam - Comp	JM400	-	JM800
Out & About (Palace)	Latex	JM400	-	JM800
Shetland	Latex Foam - Comp	JM400	-	JM800
Skye	Latex Foam - Comp	JM400	-	JM800

Tiles

Ellipse	Bitumen / Felt	JM400	JM300	-
Hexagon	Bitumen / Felt	JM400	JM300	-
Interiguard	Bitumen / Felt	JM400	JM300	-
Polygon	Bitumen / Felt	JM400	JM300	-
Radius	Bitumen / Felt	JM400	JM300	-
Triangle	Bitumen / Felt	JM400	JM300	-

ST S FLOORING DISTRIBUTORS LTD • Tel 08454 341000 • Fax 01689 870457

Arundel Twist	Jute	JM400, JM200	JM200	JM800
Ashton Twist	Woven Scrim	JM400, JM200	JM200	JM800
Ashton Twist	Felt	JM400, JM200	JM200	JM800
Blenheim Twist	Woven Synthetic	JM400, JM200	JM200	JM800
Brenwood Forest, Heather & Twist	Woven Scrim	JM400, JM200	JM200	JM800
Cherwell Cord	Felt	JM400, JM200	JM200	JM800
Chislehurst	Woven Scrim	JM400, JM200	JM200	JM800
Dorchester	Jute	JM400, JM200	JM200	JM800
Gladiator Supreme	Latex Foam	JM400	-	JM800
Harrier Felt	Felt	JM400, JM200	JM200	JM800
Heatherdale	Woven Scrim	JM400, JM200	JM200	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

Hercules	Gel Foam - Compressed	JM400	-	JM800
Kare Twist	Aqua Bac Impervious	JM400, JM200	-	JM800
Malabar	Woven Synthetic	JM400, JM200	JM200	JM800
Meadowbrook	Woven Scrim	JM400, JM200	JM200	JM800
Medicare	Gel Foam	JM400	-	JM800
Milton	Woven Synthetic	JM400, JM200	JM200	JM800
Milton	Felt	JM400, JM200	JM200	JM800
Multicare	Aqua Bac Impervious	JM400, JM200	-	JM800
Multicare	Envi Bac	JM400, JM200	JM200	JM800
New Harrier	Latex Foam	JM400	-	JM800
Opus Twist	Woven Scrim	JM400, JM200	JM200	JM800
Pall Mall	Jute Hessian	JM400, JM200	JM200	JM800
Primo Range	Woven Synthetic	JM400, JM200	JM200	JM800
Radley Twist	Woven Synthetic	JM400, JM200	JM200	JM800
Ravensbury Twist	Woven Synthetic	JM400, JM200	JM200	JM800
Suparsava Twist	Woven Synthetic	JM400, JM200	JM200	JM800
Valley Twist	Action Bac	JM400	-	JM800

Tiles

Ascot	Bitumen	JM400	JM300	-
Beckenham	Bitumen	JM400	JM300	-
Chelsfield	Bitumen	JM400	JM300	-
Cheltenham	Bitumen	JM400	JM300	-
Clipper	Bitumen	JM400	JM300	-
Croydon Stripe	Bitumen	JM400	JM300	-
Inspirations	Bitumen	JM400	JM300	-
New Croydon	Bitumen	JM400	JM300	-
New Keston	Bitumen	JM400	JM300	-
New Selsdon	Bitumen	JM400	JM300	-
Terrain	Bitumen	JM400	JM300	-
Westerham	Bitumen	JM400	JM300	-

TARKETT COMMERCIAL • Tel 01622 854286 • Fax 01622 854020

Acczent Range	Vinyl	JM500, JM700	-	*
Century Excel	Vinyl	JM500, JM700	-	*
Eclipse	Vinyl	JM500, JM700	-	*
Eminent iQ	Vinyl	JM500, JM700	-	*
Eminent Safe T	Vinyl	JM500, JM700	-	*
Gemstone	Vinyl	JM500, JM700	-	*
Granit Acoustic	Vinyl Foam	JM500, JM700	-	*
Granit iQ	Vinyl	JM500, JM700	-	*
Granit Multisafe	Vinyl	JM500, JM700	-	*
I.D Moduline	Vinyl	JM500, JM700	-	*
Megalit iQ	Vinyl	JM500, JM700	-	*
Monolit iQ	Vinyl	JM500, JM700	-	*
Olympus	Vinyl	JM500, JM700	-	*
Omnisports Excel	Vinyl Foam	JM500, JM700	-	*
Omnisports Reference	Vinyl Foam	JM500, JM700	-	*
Omnisports Speed	Vinyl Foam	JM500, JM700	-	*
Optima iQ	Vinyl	JM500, JM700	-	*
Primo Premium	Vinyl	JM500, JM700	-	*
Safetread Range	Vinyl	JM500, JM700	-	*
Somplan 500	Vinyl	JM500, JM700	-	*
Somplan Plus	Vinyl	JM500, JM700	-	*
Square Tile	Vinyl	JM500, JM700	-	*
Standard 1.5/2.0mm	Vinyl	JM500, JM700	-	*
Tapiflex Range	Vinyl	JM500, JM700	-	*
Vylon Plus	Vinyl	JM500, JM700	-	*

* for vertical bonds please refer to our technical department

TELENZO CARPETS LTD • Tel 01422 374417 • Fax 01422 377452

Amazona	Action Bac	JM400	-	JM800
Amber	Action Bac	JM400	-	JM800
Amsterdam	Action Bac	JM400	-	JM800
Belgrove	Action Bac	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Brisbane Extra	Action Bac	JM400	-	JM800
Burford Bridge	Action Bac	JM400	-	JM800
Centrepont	Action Bac	JM400	-	JM800
Chelsea	Action Bac	JM400	-	JM800
Delft	Action Bac	JM400	-	JM800
Greewhich	Action Bac	JM400	-	JM800
Hamilton	Action Bac	JM400	-	JM800
Highgrove	Action Bac	JM400	-	JM800
Jubilee	Action Bac	JM400	-	JM800
Lynton Plain	Action Bac	JM400	-	JM800
Lynton Stripe	Action Bac	JM400	-	JM800
Mainline	Action Bac	JM400	-	JM800
Nature Wool	Action Bac	JM400	-	JM800
Orinoco	Action Bac	JM400	-	JM800
Piccadilly	Action Bac	JM400	-	JM800
Rembrandt	Action Bac	JM400	-	JM800
Sydney	Action Bac	JM400	-	JM800
Windsor	Action Bac	JM400	-	JM800
Xpress	Action Bac	JM400	-	JM800

TESSERA TILES • Tel 0800 0282162 • Fax 01772 646912

Full Range	Bitumen	JM400	JM300	-
Full Range	Softbac	JM400	JM200	-
Full Range	P V C / Scrim	JM500, JM700	JM300	-

TINTAWN CARPETS LTD • Tel 01297 630647 • Fax 01297 630648

Celestial	Jute / Latex	JM400	-	JM800
Kylemore	Jute / Latex	JM400	-	JM800
Natural Heathers	Jute / Latex	JM400	-	JM800
Rusticweave	Jute / Latex	JM400	-	JM800
Shelbourne Contract	Jute / Latex	JM400	-	JM800
Simply Natural	Jute / Latex	JM400	-	JM800
Town House	Jute / Latex	JM400	-	JM800

TRETFORD CARPETS LTD • Tel 01827 312414 • Fax 01827 52092

Tretford Interland	Jute Hessian	JM400	-	JM800
Tretford Carpet Tiles	P V C	-	JM300	-

ULSTER CARPETS • Tel 02838 334433 • Fax 02838 333142

Anatolia	Jute / Synthetic / Cotton	JM400	-	JM800
Ariana	Jute / Synthetic / Cotton	JM400	-	JM800
Athenia	Jute / Synthetic / Cotton	JM400	-	JM800
Azara	Jute / Synthetic / Cotton	JM400	-	JM800
Custom Plan	Jute / Synthetic / Cotton	JM400	-	JM800
Donegal Twist	Synthetic / Cotton	JM400	-	JM800
Eclectic Elements	Synthetic / Cotton	JM400	-	JM800
Glenavy	Jute / Synthetic / Cotton	JM400	-	JM800
Glendun	Jute / Synthetic / Cotton	JM400	-	JM800
Glenmoy	Jute / Synthetic / Cotton	JM400	-	JM800
Glenshane	Jute / Synthetic / Cotton	JM400	-	JM800
Open Spaces	Synthetic / Cotton	JM400	-	JM800
Orissa	Jute / Synthetic / Cotton	JM400	-	JM800
Polar	Jute / Synthetic / Cotton	JM400	-	JM800
Quadra	Jute / Synthetic / Cotton	JM400	-	JM800
Sandscapes	Jute / Cotton	JM400, JM200	JM200	JM800
Sheriden	Jute / Synthetic / Cotton	JM400	-	JM800
Studio Twist	Jute / Cotton	JM400, JM200	JM200	JM800
Tazmin	Jute / Synthetic / Cotton	JM400	-	JM800
Ulster Velvet	Jute / Cotton	JM400, JM200	JM200	JM800
York Wilton	Jute / Cotton	JM400, JM200	JM200	JM800

VICTORIA CARPETS LTD • Tel 01562 749300 • Fax 01562 749349

Woven

Diplomat	Jute / Synthetic	JM400	-	JM800
Estrada	Jute / Synthetic	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

Executive Square	Jute / Synthetic	JM400	-	JM800
Executive Tweed	Jute / Synthetic	JM400	-	JM800
Natures Way Limestone	Jute / Cotton	JM400	-	JM800
Natures Way Sandstone	Jute / Cotton	JM400	-	JM800
Royal Twist	Jute / Synthetic	JM400	-	JM800
Super Wyndham	Jute / Synthetic	JM400	-	JM800

Tufted

Berber Ridge & Berber Stripe	Synthetic	JM400	-	JM800
Boucle	Synthetic	JM400	-	JM800
Broadway	Felt	JM400	-	JM800
Castillion	Synthetic	JM400	-	JM800
Celtic Heathers	Synthetic	JM400	-	JM800
Chenille	Synthetic	JM400	-	JM800
City Living	Synthetic	JM400	-	JM800
Crown Twist	Synthetic	JM400	-	JM800
Duchess Elite	Synthetic	JM400	-	JM800
Eton Square	Synthetic	JM400	-	JM800
Gaelic Heathers	Synthetic	JM400	-	JM800
Kelso	Synthetic	JM400	-	JM800
La Premier Collection	Synthetic	JM400	-	JM800
Mahattan Square	Synthetic	JM400	-	JM800
Natural Accent	Synthetic	JM400	-	JM800
Regal Twist	Synthetic	JM400	-	JM800
Royal Eminence	Synthetic	JM400	-	JM800
Sisal Weave	Synthetic	JM400	-	JM800
Suede	Synthetic	JM400	-	JM800
Tree Bark	Synthetic	JM400	-	JM800
Tudor Manor	Synthetic	JM400	-	JM800
Tudor Twist	Synthetic	JM400	-	JM800
Tudor Twist Elite	Synthetic	JM400	-	JM800
Tudor Twist Supreme	Synthetic	JM400	-	JM800
Vibrant	Synthetic	JM400	-	JM800
Wool Tweed	Synthetic	JM400	-	JM800

WARLORD CONTRACT CARPETS LTD • Tel 01453 821800 • Fax 01453 791167

Delta Cord Sheet	Fibrebonded	JM400	-	JM800
Delta Plus Sheet	Fibrebonded	JM400	-	JM800
Highgrove	Action Bac	JM400, JM200	JM200	JM800
Martred / Warlord Sheet	Fibrebonded	JM400	-	JM800
Orbis	Impervious Foam	JM400	-	JM800
Parade	Synthetic	JM400	-	JM800
Saxon Velour Sheet	Fibrebonded	JM400	-	JM800
Seasons	Impervious Felt	JM400, JM200	JM200	JM800
Trident Broadcord Sheet	Synthetic	JM400	-	JM800

Tiles

Amberley	Bitumen / Felt	JM400	JM300	-
Any Which Way	Bitumen / Felt	JM400	JM300	-
Burford	Bitumen / Felt	JM400	JM300	-
Camouflage	P V C	JM500, JM700	JM300	-
Chedworth	Bitumen / Felt	JM400	JM300	-
Delta Cord	Bitumen / Felt	JM400	JM300	-
Delta Plus	Bitumen / Felt	JM400	JM300	-
Dursley	Bitumen / Felt	JM400	JM300	-
Frome	Bitumen / Felt	JM400	JM300	-
Glencoe	Bitumen / Felt	JM400	JM300	-
Livingston	P V C	JM400	JM300	-
Marling Twill	Bitumen / Felt	JM400	JM300	-
Montrose	Bitumen / Felt	JM400	JM300	-
Naturals	Bitumen / Felt	JM400	JM300	-
Parade	Bitumen / Felt	JM400	JM300	-
Saxon Velours	Bitumen / Felt	JM400	JM300	-
Seasons	Bitumen / Felt	JM400	JM300	-
Sumi Green	P V C	JM400	JM300	-

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL
Sumi Leaf	P V C	JM400	JM300	-
Sumi Marine	P V C	JM400	JM300	-
Trident	Comfort Bac	JM400	JM300	-
Trident Broadcord	Bitumen / Felt	JM400	JM300	-
Trilogy Collection	Bitumen / Felt	JM400	JM300	-

WESTEX CARPETS LTD • Tel 01274 861334 • Fax 01274 873266

100% Wool Loop Collection	Jute	JM400, JM200	JM200	JM800
Barcode Design	Jute	JM400, JM200	JM200	JM800
Contemporary Design	Jute	JM400, JM200	JM200	JM800
Contract Twist 10	Jute	JM400, JM200	JM200	JM800
Contract Twist 8	Jute	JM400, JM200	JM200	JM800
Cube Design	Jute	JM400, JM200	JM200	JM800
Designer Collection	Jute	JM400, JM200	JM200	JM800
Harmony Velvet	Jute	JM400, JM200	JM200	JM800
Lattice Design	Jute	JM400, JM200	JM200	JM800
Luxury 100% Wool Collection	Jute	JM400, JM200	JM200	JM800
Matrix design	Jute	JM400, JM200	JM200	JM800
Medley design	Jute	JM400, JM200	JM200	JM800
Menuet Design	Jute	JM400, JM200	JM200	JM800
Penulitima	Jute	JM400, JM200	JM200	JM800
Quartet Stripe & Velvet	Jute	JM400, JM200	JM200	JM800
Symphony	Jute	JM400, JM200	JM200	JM800
Traditional Twist	Jute	JM400, JM200	JM200	JM800
Trellis Design	Jute	JM400, JM200	JM200	JM800
Ultima Twist Collection	Jute	JM400, JM200	JM200	JM800
West End Velvet Collection	Jute	JM400, JM200	JM200	JM800

WESTON CARPETS • Tel 0845 644 9090 • Fax 0845 644 9191

Sheet

Weston Axminster	Woven	JM400	-	JM800
Weston Classic	Impervious Latex	JM400	-	JM800
Weston Décor Care Designer Collection	Impervious Latex	JM400	-	JM800
Weston Denver	Textile	JM400	-	JM800
Weston Imperial Boucle	Textile	JM400	-	JM800
Weston Maroc	Textile	JM400	-	JM800
Weston Natural Textures Diamond	Textile	JM400	-	JM800
Weston Natural Textures Tonal	Textile	JM400	-	JM800
Weston Oklahoma	Textile	JM400	-	JM800
Weston Premiere Care Rosetta	Impervious Felt	JM400, JM200	JM200	JM800
Weston Queen Tweed	Felt	JM400, JM200	JM200	JM800
Weston Queen Tweed	Textile	JM400	-	JM800
Weston Ritz	Textile	JM400	-	JM800
Weston Royal Boucle	Textile	JM400	-	JM800
Weston Royal Design	Textile	JM400	-	JM800
Weston Royal Tweed	Textile	JM400	-	JM800
Weston Royal Velour	Textile	JM400	-	JM800
Weston Sisal Boucle	Impervious Latex	JM400, JM200	JM200	JM800
Weston Stone Fibre Collection	Impervious Latex	JM400	-	JM800
Weston Supreme Boucle	Textile	JM400	-	JM800
Weston Supreme Stripe	Textile	JM400	-	JM800
Weston Tunis	Felt	JM400, JM200	JM200	JM800
Weston Tunis	Textile	JM400	-	JM800

WHITESTONE WEAVERS LTD • Tel 01642 242423 • Fax 01642 757628

Balmoral Fine Velvet	Woven	JM400	-	JM800
Barrington	Woven	JM400	-	JM800
Bishops Court	Woven	JM400	-	JM800
Casablanca	Jute	JM400, JM200	JM200	JM800
Cathedral Naturals	Woven	JM400	-	JM800
Classic Tonals	Woven	JM400	-	JM800
Countrystone Twist	Jute	JM400, JM200	JM200	JM800
Craftstone Elite Twist 50 / 60	Jute	JM400, JM200	JM200	JM800
Designer Collection	Woven	JM400	-	JM800
Durham Cathedral	Woven	JM400	-	JM800

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

Durham Edition	Jute	JM400, JM200	JM200	JM800
Durham Super 40	Jute	JM400, JM200	JM200	JM800
Durham Supreme 50	Jute	JM400, JM200	JM200	JM800
Durham Twist 30	Jute	JM400, JM200	JM200	JM800
Durham Twist Elite	Jute	JM400, JM200	JM200	JM800
Durham Vel Supreme	Jute	JM400, JM200	JM200	JM800
Durham Velvet	Jute	JM400, JM200	JM200	JM800
Edwardian	Woven	JM400	-	JM800
Featherstone Twist	Jute	JM400, JM200	JM200	JM800
Finestone Twist	Jute	JM400, JM200	JM200	JM800
Flagstone Twist	Jute	JM400, JM200	JM200	JM800
Georgian	Woven	JM400	-	JM800
Keystone Twist	Jute	JM400, JM200	JM200	JM800
Natural Tones	Woven	JM400	-	JM800
Natural Weave	Jute	JM400, JM200	JM200	JM800
Natures Own	Woven	JM400	-	JM800
Prince Bishop	Woven	JM400	-	JM800
Tartan Collection	Woven	JM400	-	JM800
Tudor Palace	Woven	JM400	-	JM800
Verona	Woven	JM400	-	JM800
Weaver Stone Twist Supreme	Jute	JM400, JM200	JM200	JM800

THE WILTON CARPET FACTORY LTD • Tel 01722 742890 • Fax 01722 742923

Bespoke Axminster	Jute	JM400	-	JM800
Bespoke Axminster	Poly	JM400, JM200	JM200	JM800
Pattern Plan Axminster	Jute	JM400	-	JM800
Pattern Plan Axminster	Poly	JM400, JM200	JM200	JM800
Stock Ranges	Jute	JM400	-	JM800

WOLFF CONTRACT CARPET MILLS LTD • Tel 01827 310111 • Fax 01827 316553

Alpha Cord	Latex	JM400	-	JM800
Baccarat	Textile	JM400	-	JM800
Candidate	Felt	JM400	-	JM800
Charterhouse Range	Jute	JM400	-	JM800
Custom Care Plus	Impervious Foam	JM400	-	JM800
Double Strike II	Gel Foam	JM400	-	JM800
Flagstaff	Gel	JM400	-	JM800
Invasion II	Secondary	JM400	-	JM800
Medi-Excel	Impervious Foam	JM400	-	JM800
Medi-Supreme	Impervious Foam	JM400	-	JM800
New Residence	Impervious Foam	JM400	-	JM800
Oakhham	Action Bac	JM400	-	JM800
Oban	Impervious Foam	JM400	-	JM800
Onyx Stone	P V C	JM500, JM700	-	*
Orchard Wood Plank	P V C	JM500, JM700	-	*
Pattani	Bitumen / Felt	JM400	JM300	-
Protector	Impervious Foam	JM400	-	JM800
Rubix Tile	P V C	JM500, JM700	JM300	-
Rutland	Jute	JM400	-	JM800
Safeguard Vinyl II	Gel	JM400	-	JM800
Shimia Tile	Bitumen / Felt	JM400	JM300	-
Siam Tile	Bitumen / Felt	JM400	JM300	-
Similan II	Bitumen / Felt	JM400	-	JM800
Stalwart	Impervious Foam	JM400	-	JM800
Surin Tile	Bitumen / Felt	JM400	JM300	-
Tetris Tile	Bitumen / Felt	JM400	JM300	-
Universal	Impervious Foam	JM400	-	JM800
Universal Lite	Impervious Foam	JM400	-	JM800
Universal Plain	Impervious Foam	JM400	-	JM800
Waterford Twist	Secondary	JM400	-	JM800
Yeoman	Jute	JM400	-	JM800

* for vertical bonds please refer to our technical department

TRADE NAME	BACKING	TYPE OF BOND		
		PERMANENT	RELEASE	VERTICAL

WOLLIMEX • Tel 01827 831420 • Fax 01827 831421

Tiles				
Alps 7500	Bitumen	JM400	JM300	-
Battleaxe	Bitumen	JM400	JM300	-
Broadsword	Bitumen	JM400	JM300	-
Catalan	Bitumen	JM400	JM300	-
Creative	Bitumen	JM400	JM300	-
Crossbow	Bitumen	JM400	JM300	-
Design 200	Bitumen	JM400	JM300	-
Ibiza	Bitumen	JM400	JM300	-
Lucern	Bitumen	JM400	JM300	-
Mainstay	Bitumen	JM400	JM300	-
Malaga	Bitumen	JM400	JM300	-
Partners	Bitumen	JM400	JM300	-
Seville	Bitumen	JM400	JM300	-
Signature	Bitumen	JM400	JM300	-
Tipo	Bitumen	JM400	JM300	-
Toledo	Bitumen	JM400	JM300	-
Valencia	Bitumen	JM400	JM300	-

Sheet				
Archer	Felt	JM400	-	JM800
Balmoral	Action Bac	JM400	JM300	JM800
Classic 1000	Action Bac	JM400	JM300	JM800
Classic 1200	Action Bac	JM400	JM300	JM800
Classic 1400	Action Bac	JM400	JM300	JM800
Classic Wool	Action Bac	JM400	JM300	JM800
Claymore	Action Bac	JM400	JM300	JM800
Crusader Twist 30/40/50	Jute	JM400	JM300	JM800
Crystal	Impervious	JM400	-	JM800
Javlin	Impervious	JM400	-	JM800
Mosaic	Impervious	JM400	-	JM800
New Gauntlet	Impervious	JM400	-	JM800
Newmarket II	Action Bac	JM400	JM300	JM800
Accommodation Twist	Secondary	JM400	JM300	JM800
Signature Lite	Secondary	JM400	JM300	JM800
Templar	Secondary	JM400	JM300	JM800
Shield	Impervious	JM400	-	JM800

Matting				
All Weather	Latex	JM400	-	JM800
Basel	Gel	JM400	-	JM800
Brosmat	Compact Gran. Rubber / Latex	JM900	-	JM800
Caretaker	Compact Gran. Rubber / Latex	JM900	-	JM800
Davos	Gel	JM400	-	JM800
Design 100	Gran. Rubber	JM900	-	JM800
Design 300	Gran. Rubber	JM900	-	JM800
Design 400	Gran. Rubber	JM900	-	JM800
Fairway	Compact Gran. Rubber / Latex	JM900	-	JM800
Fairway	Compact Gran. Rubber / Latex	JM900	-	JM800
Geneva	Waffle	JM400	-	JM800
Golf	Compact Gran. Rubber / Latex	JM900	-	JM800
Lancer	Gel	JM400	-	JM800
Lionheart	Gel	JM400	-	JM800
Partners Sheet	Latex	JM400	-	JM800
Vierbier	Gel	JM400	-	JM800
Zermatt Hobnail	Latex Waffle	JM400	-	JM800
Zermatt Wave	Latex Waffle	JM400	-	JM800
Zurich	Duo Back	JM400	-	JM800

ZENO - PROTECT • Tel 01423 865011 • Fax 01423 862679

Protect Solution	P V C / Rubber	JM900	-	-
Protect Super	P V C / Rubber	JM900	-	-

Lined area for notes with horizontal green bars.

morleys 
limited
stairnosings & flooring accessories

morleys limited, unit 2, higher walton mill,
higher walton, preston pr5 4dj

tel. 01772 626700

fax. 01772 627372

e-mail. sales@morleysltd.co.uk

website. www.morleysltd.co.uk